

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 1/18



## Paint Tech Evo white (plast) 500ml

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name/designation:

Paint Tech Evo white (plast) 500ml

Article No.:

T120252

UFI:

6XQ1-PGK3-M5QW-P101

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Spray paint

Relevant identified uses:

**Product Categories [PC]**

**PC 9a:** Coatings and paints, thinners, paint removers

**Process categories [PROC]**

**PROC 7:** Industrial spraying

**PROC 11:** Non industrial spraying

#### \* 1.3. Details of the supplier of the safety data sheet

Supplier:

**KANDO Service GmbH**

Hartleitnerstraße 3

4653 Eberstälzell

Austria

**Telephone:** +43 (0) 7241 213 79

**E-mail:** msds@kando.eu

#### 1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2



Page 2/18

## Paint Tech Evo white (plast) 500ml

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



**GHS07**

Exclamation mark



**GHS02**

Flame

**Signal word:** Danger

**Hazard components for labelling:**

acetone; n-butyl acetate; 2-methoxy-1-methylethyl acetate; butan-1-ol

Hazard statements for physical hazards	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazards	
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.

Precautionary statements Storage	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal	
P501	Dispose of the contents/container in accordance with regional regulations.

**Additional information:**

Formation of explosive mixtures possible without adequate ventilation.

### 2.3. Other hazards

**Other adverse effects:**

The product does not meet the PBT/vPvB criteria.

Determination of endocrine disrupting properties: not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 3/18



## Paint Tech Evo white (plast) 500ml

### SECTION 3: Composition/information on ingredients

#### \* 3.2. Mixtures

##### Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-64-1 EC No.: 200-662-2 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	<b>acetone</b> Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066 <b>Acute Toxicity Estimate</b> ATE (oral) 5,800 mg/kg ATE (dermal) 20,000 mg/kg ATE (inhalation, gases) 76 ppmV ATE (inhalation, vapour) 76 mg/L ATE (inhalation, dust/mist) 76 mg/L <b>Additional information:</b> EUH066	25 - < 50 %
CAS No.: 115-10-6 EC No.: 204-065-8 Index No.: 603-019-00-8 REACH No.: 01-2119472128-37	<b>dimethyl ether</b> Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger <b>Acute Toxicity Estimate</b> ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) 308.5 ppmV ATE (inhalation, dust/mist) 308.5 mg/L	20 - < 25 %
CAS No.: 123-86-4 EC No.: 204-658-1 Index No.: 607-025-00-1 REACH No.: 01-2119485493-29	<b>n-butyl acetate</b> Flam. Liq. 3 (H226), STOT SE 3 (H336) Warning EUH066 <b>Acute Toxicity Estimate</b> ATE (oral) 10,800 mg/kg ATE (dermal) > 17,600 mg/kg ATE (inhalation, gases) > 21 ppmV ATE (inhalation, vapour) > 21 mg/L <b>Additional information:</b> EUH066	10 - < 12.5 %
CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21	<b>propane</b> Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger <b>Acute Toxicity Estimate</b> ATE (oral) 5,840 mg/kg ATE (dermal) 13,900 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) ≥ 50 mg/L	5 - < 10 %
CAS No.: 108-65-6 EC No.: 203-603-9 Index No.: 607-195-00-7 REACH No.: 01-2119475791-29	<b>2-methoxy-1-methylethyl acetate</b> Flam. Liq. 3 (H226), STOT SE 3 (H336) Warning <b>Acute Toxicity Estimate</b> ATE (oral) 8,560 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, gases) > 10,000 ppmV ATE (inhalation, vapour) > 10 mg/L	5 - < 10 %
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	<b>Butane (with &lt; 0,1 % butadiene (203-450-8))</b> Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger <b>Acute Toxicity Estimate</b> ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) 658 ppmV ATE (inhalation, vapour) > 800,000 mg/L	5 - < 10 %

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 4/18



## Paint Tech Evo white (plast) 500ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 13463-67-7 EC No.: 236-675-5 Index No.: 022-006-00-2 REACH No.: 01-2119489379-17	<b>titanium dioxide</b> Carc. 2 (H351) ⚠ Warning <b>Acute Toxicity Estimate</b> ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) 5 mg/L ATE (inhalation, dust/mist) 3.43 – 5.09 mg/L	5 – < 10 %
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	<b>Isobutane (contains &lt; 0.1% butadiene (203-450-8))</b> Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) ⚠ Danger	2.5 – < 5 %
CAS No.: 9004-70-0	<b>Cellulosenitrat</b> Expl. 1.1 (H201) ⚠ Danger <b>Additional information:</b> CLP Note T	< 2.5 %
CAS No.: 71-36-3 EC No.: 200-751-6 Index No.: 603-004-00-6 REACH No.: 01-2119484630-38	<b>butan-1-ol</b> Acute Tox. 4 (H302), Eye Dam. 1 (H318), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336), Skin Irrit. 2 (H315) ⚠⚠⚠ Danger <b>Acute Toxicity Estimate</b> ATE (oral) 2,292 mg/kg ATE (dermal) 3,430 mg/kg ATE (inhalation, gases) 17,000 ppmV ATE (inhalation, vapour) 17 mg/L ATE (inhalation, dust/mist) 17,000 mg/L	≥ 1 – < 2.5 %

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

#### In case of skin contact:

In general, the product is not irritating to skin.

#### After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

#### Following ingestion:

Drink plenty of water. Provide fresh air. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Adapt fire extinguishing measures to the surroundings.

### 5.2. Special hazards arising from the substance or mixture

Formation of toxic gases when heated or in case of fire.

### 5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 19 Aug 2025

**Print date:** 20 Aug 2025

**Version:** 2

Page 5/18



## Paint Tech Evo white (plast) 500ml

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

**Personal precautions:**

Provide adequate ventilation. Use appropriate respiratory protection. Wear protective equipment. Keep unprotected persons away. Keep away from sources of ignition - No smoking.

##### 6.1.2. For emergency responders

No data available

#### 6.2. Environmental precautions

Do not allow to enter drains/surface water/ground water.

#### 6.3. Methods and material for containment and cleaning up

**Other information:**

Dispose of contaminated material as waste according to section 13. Provide adequate ventilation.

#### 6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Protective measures**

**Advices on safe handling:**

Ensure good ventilation/extraction at the workplace.

**Fire prevent measures:**

Do not spray against a flame or on a glowing object. Keep away from sources of ignition - No smoking. Have breathing apparatus ready.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Requirements for storage rooms and vessels:**

The official regulations for the storage of pressurised gas packages must be observed.

**Hints on storage assembly:**

Not required.

**Storage class (TRGS 510, Germany):** 2B - Aerosol dispensers and lighters

**Further information on storage conditions:**

Keep container tightly closed.

#### 7.3. Specific end use(s)

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 6/18



## Paint Tech Evo white (plast) 500ml

### SECTION 8: Exposure controls/personal protection

#### \* 8.1. Control parameters

##### 8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	② 2,000 ppm (4,800 mg/m <sup>3</sup> ) ⑤ (max. 4x15 min./Schicht)
IOELV (EU)	<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m <sup>3</sup> )
MAK (AT)	<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,200 mg/m <sup>3</sup> )
MAK (AT)	<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	① 1,000 ppm (1,910 mg/m <sup>3</sup> )
MAK (AT)	<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	② 2,000 ppm (3,820 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./Schicht, Momentanwert)
IOELV (EU)	<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	① 1,000 ppm (1,920 mg/m <sup>3</sup> )
MAK (AT) from 10 Apr 2021	<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	① 50 ppm (241 mg/m <sup>3</sup> ) ② 100 ppm (480 mg/m <sup>3</sup> )
IOELV (EU) from 20 Nov 2019	<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	① 50 ppm (241 mg/m <sup>3</sup> ) ② 150 ppm (723 mg/m <sup>3</sup> )
MAK (AT)	<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9	② 2,000 ppm (3,600 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	<b>propane</b> CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m <sup>3</sup> )
MAK (AT)	<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	② 100 ppm (550 mg/m <sup>3</sup> ) ⑤ (max. 8x5 min./Schicht, Momentanwert, kann über die Haut aufgenommen werden) H
IOELV (EU)	<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (275 mg/m <sup>3</sup> ) ② 100 ppm (550 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)
MAK (AT)	<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (275 mg/m <sup>3</sup> ) ⑤ (kann über die Haut aufgenommen werden) H
MAK (AT)	<b>Butane (with &lt; 0,1 % butadiene (203-450-8))</b> CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m <sup>3</sup> )
MAK (AT)	<b>Butane (with &lt; 0,1 % butadiene (203-450-8))</b> CAS No.: 106-97-8 EC No.: 203-448-7	② 1,600 ppm (3,800 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./Schicht, Momentanwert)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2



Page 7/18

## Paint Tech Evo white (plast) 500ml

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT) from 11 Sept 2007	<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	② 10 mg/m <sup>3</sup> ⑤ (alveolengängige Fraktion, max. 2x60 min./Schicht)
MAK (AT) from 11 Sept 2007	<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5	① 5 mg/m <sup>3</sup> ⑤ (alveolengängige Fraktion)
MAK (AT)	<b>Isobutane (contains &lt; 0.1% butadiene (203-450-8))</b> CAS No.: 75-28-5 EC No.: 200-857-2	② 1,600 ppm (3,800 mg/m <sup>3</sup> ) ⑤ (max. 3x60 min./SchichtMomentanwert)
MAK (AT)	<b>Isobutane (contains &lt; 0.1% butadiene (203-450-8))</b> CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m <sup>3</sup> )
MAK (AT)	<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	① 50 ppm (150 mg/m <sup>3</sup> )
MAK (AT)	<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	② 200 ppm (600 mg/m <sup>3</sup> ) ⑤ (max. 4x15 min./Schicht)

### 8.1.2. Biological limit values

No data available

### 8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	1,210 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	200 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	2,420 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, local effects
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	186 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	1,894 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	471 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	300 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2



Page 8/18

## Paint Tech Evo white (plast) 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	35.7 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	600 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	859.7 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	300 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	35.7 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, local effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	600 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, local effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	300 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, local effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	11 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	5 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	11 mg/kg bw/ day	① DNEL worker ② Acute - dermal, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	5 mg/kg bw/ day	① DNEL Consumer ② Acute - dermal, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	2 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	2 mg/kg bw/ day	① DNEL Consumer ② Acute - oral, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	275 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	33 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	796 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	320 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	36 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	310 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2



Page 9/18

## Paint Tech Evo white (plast) 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	55 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, local effects
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	3.125 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	10.6 mg/L	① PNEC aquatic, freshwater
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	1.06 mg/L	① PNEC aquatic, marine water
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	100 mg/L	① PNEC sewage treatment plant
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	30.4 mg/kg	① PNEC sediment, freshwater
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	3.04 mg/kg	① PNEC sediment, marine water
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	29.5 mg/kg	① PNEC soil
<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2	21 mg/L	① PNEC aquatic, intermittent release
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	0.155 mg/L	① PNEC aquatic, freshwater
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	0.016 mg/L	① PNEC aquatic, marine water
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	0.681 mg/kg	① PNEC sediment, freshwater
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	0.069 mg/kg	① PNEC sediment, marine water
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	0.045 mg/kg	① PNEC soil
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8	1.549 mg/L	① PNEC aquatic, intermittent release
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.18 mg/L	① PNEC aquatic, freshwater
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.015 mg/L	① PNEC aquatic, marine water
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	35.6 mg/L	① PNEC sewage treatment plant
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.981 mg/L	① PNEC sediment, freshwater

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2



Page 10/18

## Paint Tech Evo white (plast) 500ml

Substance name	PNEC Value	① PNEC type
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.0981 mg/L	① PNEC sediment, marine water
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.0903 mg/kg	① PNEC soil
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1	0.36	① PNEC aquatic, intermittent release
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	0.0635 mg/L	① PNEC aquatic, freshwater
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	0.0064 mg/L	① PNEC aquatic, marine water
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	100 mg/L	① PNEC sewage treatment plant
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	3.29 mg/L	① PNEC sediment, freshwater
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	0.329 mg/L	① PNEC sediment, marine water
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9	0.29 mg/kg	① PNEC soil
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	0.082 mg/L	① PNEC aquatic, freshwater
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	0.0082 mg/L	① PNEC aquatic, marine water
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	2,476 mg/L	① PNEC sewage treatment plant
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	0.178 mg/kg	① PNEC sediment, freshwater
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	0.0178 mg/kg	① PNEC sediment, marine water
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	0.015 mg/kg	① PNEC soil
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6	2.25 mg/L	① PNEC aquatic, intermittent release

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No further details. See section 7.

### 8.2.2. Personal protection equipment



#### Eye/face protection:

Tight-fitting safety goggles

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 19 Aug 2025

**Print date:** 20 Aug 2025

**Version:** 2



Page 11/18

## Paint Tech Evo white (plast) 500ml

### Skin protection:

Hand protection:

Wear protective gloves.

Glove material: Butyl caoutchouc (butyl rubber); The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer.

Penetration time of the glove material: Gloves made of butyl rubber with a material thickness of 0.4mm are resistant to: Acetone 480 min; Butyl acetate 60 min; Ethyl acetate 170 min; Xylene 42 min. Gloves made of butyl rubber with a layer thickness of 0.4 mm are resistant to solvents for 42 - 480 minutes. As a precautionary measure, we recommend users and those responsible for occupational safety to take a resistance of 42 minutes as a basis. Taking into account the information in chapter 3 of the MSDS, it is possible to assume a higher resistance in individual cases.

### Respiratory protection:

In case of short or low exposure use breathing filter apparatus; in case of intensive or prolonged exposure use self-contained breathing apparatus. Filter A2/P2

### Other protection measures:

General protective and hygienic measures: Keep away from food, drink and animal feed. Remove contaminated, saturated clothing immediately. Wash hands before breaks and after work. Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

### 8.2.3. Environmental exposure controls

No data available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

**Form:** Aerosol

**Odour:** solvent-like

**Colour:** According to product designation

**flammability:** No data available

#### Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		② insoluble in: Water
Melting point	<i>No data available</i>		
Freezing point	<i>No data available</i>		
Initial boiling point and boiling range	<i>not applicable</i>		② Aerosol
Flash point	<i>not applicable</i>		② Aerosol
Evaporation rate	<i>No data available</i>		
Auto-ignition temperature	240 °C		
Upper/lower flammability or explosive limits	1.2 - 26.2 Vol-%		
Vapour pressure	4,000 hPa	20 °C	
Vapour density	<i>No data available</i>		
Density	0.8 g/cm <sup>3</sup>	20 °C	
Bulk density	<i>not applicable</i>		
Water solubility	Immiscible		
Dynamic viscosity	<i>No data available</i>		
Kinematic viscosity	<i>No data available</i>		

### 9.2. Other information

Organic solvents: 87,3 %

VOC limit value: 678,5 g/l, 87,28 %

Solid content: 11,3 %

#### 9.2.1. Information with regard to physical hazard classes

##### Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 12/18



## Paint Tech Evo white (plast) 500ml

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No further relevant information available.

#### 10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

#### 10.4. Conditions to avoid

No further relevant information available.

#### 10.5. Incompatible materials

No further relevant information available.

#### 10.6. Hazardous decomposition products

No dangerous decomposition products known.

### SECTION 11: Toxicological information

#### \* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2
<b>ATE (oral):</b> 5,800 mg/kg
<b>ATE (dermal):</b> 20,000 mg/kg
<b>ATE (inhalation, vapour):</b> 76 mg/L
<b>ATE (inhalation, dust/mist):</b> 76 mg/L
<b>LD<sub>50</sub> oral:</b> 5,800 mg/kg (Rat)
<b>LD<sub>50</sub> dermal:</b> >15,800 mg/kg (Rabbit)
<b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> 76 ppmV 4 h (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> 5,540 mg/L 4 d (Oncorhynchus mykiss (Rainbow trout))
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 76 mg/L 4 h (Rat)
<b>n-butyl acetate</b> CAS No.: 123-86-4 EC No.: 204-658-1
<b>LD<sub>50</sub> oral:</b> 10,800 mg/kg (Rat) OECD 401
<b>LD<sub>50</sub> dermal:</b> >17,600 mg/kg (Rabbit)
<b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> >21 ppmV 4 h (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> >21 mg/L 4 h (Rat)
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9
<b>LD<sub>50</sub> oral:</b> 8,560 mg/kg (Rat)
<b>LD<sub>50</sub> dermal:</b> >5,000 mg/kg (Rabbit) OECD 402
<b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> >10,000 ppmV 4 h (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> >10 mg/L 4 h (Rat)
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6
<b>LD<sub>50</sub> oral:</b> 2,292 mg/kg (Rat)
<b>LD<sub>50</sub> dermal:</b> 3,430 mg/kg (Rabbit)
<b>LC<sub>50</sub> Acute inhalation toxicity (gas):</b> 17,000 ppmV 4 h (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> 17 mg/L 4 h (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 17,000 mg/L 4 h (Rat)

#### Skin corrosion/irritation:

Based on available data, the classification criteria are not met.  
No irritant effect.

#### Serious eye damage/irritation:

Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 13/18



## Paint Tech Evo white (plast) 500ml

### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.  
No sensitising effect known.

### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

### Carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity:

Based on available data, the classification criteria are not met.

### STOT-single exposure:

May cause drowsiness or dizziness.

### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

### Aspiration hazard:

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties:

None of the ingredients are included.

## SECTION 12: Ecological information

### \* 12.1. Toxicity

<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2
LC <sub>50</sub> : 8,300 mg/L 4 d (fish)
LC <sub>50</sub> : 8,450 mg/L 2 d (crustaceans, water flea)
LC <sub>50</sub> : 8,300 mg/L 4 d (fish)
EC <sub>50</sub> : 7,200 mg/L 4 d (Algae/water plant)
EC <sub>50</sub> : 7,200 mg/L 4 d (Alge)
EC <sub>50</sub> : 8,800 mg/L (Daphnia magna)
NOEC: 2,212 mg/L (crustaceans, Daphnia magna)
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8
LC <sub>50</sub> : >4,000 mg/L 2 d (crustaceans, Daphnia magna)
LC <sub>50</sub> : >4,000 mg/L 4 d (fish)
EC <sub>50</sub> : 155 mg/L 4 d (Algae/water plant)
LC <sub>50</sub> : >4,000 mg/L 2 d (daphnia magna)
EC <sub>50</sub> : 155 mg/L 4 d (Alge)
EC <sub>50</sub> : 155 mg/L 4 d (algae)
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9
LC <sub>50</sub> : <180 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
LC <sub>50</sub> : 18 - 24 mg/L 4 d (fish, Pimephales promelas (fathead minnow))
LC <sub>50</sub> : 100 - 180 mg/L 4 d (fish, Regenbogenforelle)
EC <sub>50</sub> : >400 mg/L 2 d (crustaceans, Daphnia magna)
EC <sub>50</sub> : 10 mg/L (Activated sludge) OECD 204
EC <sub>50</sub> : >500 mg/L 2 d (crustaceans, daphnia magna)
NOEC: 47.5 mg/L (fish, Oryzias latipes)
NOEC: 100 mg/L (crustaceans, Daphnia magna)
IC <sub>50</sub> : >25,000 mg/L 4 d (fish, Danio rerio (zebrafish))
ErC <sub>50</sub> : >85 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) OECD 203

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 14/18



## Paint Tech Evo white (plast) 500ml

<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6
<b>LC<sub>50</sub></b> : 1,376 mg/L 4 d (fish)
<b>LC<sub>50</sub></b> : 1,376 mg/L 4 d (fish)
<b>LC<sub>50</sub></b> : 1,376 mg/L 4 d (fish)
<b>EC<sub>50</sub></b> : 225 mg/L (Selenastrum capricornutum)
<b>NOEC</b> : 4.1 mg/L 21 d (Daphnia magna)
<b>EC<sub>50</sub></b> : 1,328 mg/L 2 d (Daphnia magna)

### 12.2. Persistence and degradability

<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2
<b>Biodegradation</b> : Yes, rapidly
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9
<b>Biodegradation</b> : Yes, rapidly
<b>Isobutane (contains &lt; 0.1% butadiene (203-450-8))</b> CAS No.: 75-28-5 EC No.: 200-857-2
<b>Biodegradation</b> : Yes, rapidly

### 12.3. Bioaccumulative potential

<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2
<b>Log K<sub>ow</sub></b> : -0.24
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9
<b>Log K<sub>ow</sub></b> : 1.2

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

<b>acetone</b> CAS No.: 67-64-1 EC No.: 200-662-2
<b>Results of PBT and vPvB assessment</b> : —
<b>dimethyl ether</b> CAS No.: 115-10-6 EC No.: 204-065-8
<b>Results of PBT and vPvB assessment</b> : —
<b>2-methoxy-1-methylethyl acetate</b> CAS No.: 108-65-6 EC No.: 203-603-9
<b>Results of PBT and vPvB assessment</b> : —
<b>titanium dioxide</b> CAS No.: 13463-67-7 EC No.: 236-675-5
<b>Results of PBT and vPvB assessment</b> : —
<b>Isobutane (contains &lt; 0.1% butadiene (203-450-8))</b> CAS No.: 75-28-5 EC No.: 200-857-2
<b>Results of PBT and vPvB assessment</b> : —
<b>butan-1-ol</b> CAS No.: 71-36-3 EC No.: 200-751-6
<b>Results of PBT and vPvB assessment</b> : —

The product does not meet the PBT/vPvB criteria.

### 12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

### 12.7. Other adverse effects

water hazard class 1: slightly hazardous to water

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

## SECTION 13: Disposal considerations

### \* 13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter drains/surface water/ground water. Full and empty containers are to be disposed of by private end users at the responsible hazardous waste collection centre.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2



Page 15/18

## Paint Tech Evo white (plast) 500ml

### 13.1.1. Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV

##### Waste code product

08 01 11 *	Waste paint and varnish containing organic solvents or other dangerous substances
------------	---

\*: Evidence for disposal must be provided.

##### Waste code packaging




15 01 04	metallic packaging
----------	--------------------

#### Waste treatment options

##### Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

## SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.1. UN number or ID number</b>			
UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, Flammable
<b>14.3. Transport hazard class(es)</b>			
 2.1	No data available	 2.1	 2.1
<b>14.4. Packing group</b>			
		-	
<b>14.5. Environmental hazards</b>			
No data available	No data available	No data available	No data available
<b>14.6. Special precautions for user</b>			
<b>Special Provisions:</b> Attention: Gases <b>Limited quantity (LQ):</b> 1L <b>Excepted Quantities (EQ):</b> E0 <b>Classification code:</b> 5F <b>Tunnel restriction code:</b> (D) <b>Remark:</b> Transport category 2	No data available	<b>Special Provisions:</b> Attention: Gases <b>Limited quantity (LQ):</b> 1L <b>Excepted Quantities (EQ):</b> E0 <b>EmS-No.:</b> F-D,S-U <b>Remark:</b> Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:	<b>Special Provisions:</b> Attention: Gases

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 16/18



## Paint Tech Evo white (plast) 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
		Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.	

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU legislation

##### Restrictions on use:

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients are included.

Seveso category P3a FLAMMABLE AEROSOLS

Quantity threshold (in tons) for use in lower class farms 150t

Quantity threshold (in tons) for use in upper-tier establishments 500t

Regulation (EC) 2019/1021 [POP Regulation] None of the ingredients are included.

Regulation (EC) No 1907/2006 ANNEX XVII Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II None of the ingredients are included.

Substances of Very High Concern (SVHC) according to REACH, Article 57 None of the ingredients are included.

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 678.5 g/L

#### 15.1.2. National regulations

No data available

### 15.2. Chemical Safety Assessment

No data available

## SECTION 16: Other information

### \* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
3.2.	Mixtures
8.1.	Control parameters
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
13.1.	Waste treatment methods
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

Limit value / limit values updated: DE, SI

### \* 16.2. Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

DNEL derived no-effect level

EC<sub>50</sub> Effective Concentration 50%

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 20 Aug 2025

Version: 2

Page 17/18



## Paint Tech Evo white (plast) 500ml

ES	Exposure scenario
EWC	European Waste Catalogue
IC <sub>50</sub>	Inhibition Concentration 50 %
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC <sub>50</sub>	Lethal (fatal) Concentration 50%
LD <sub>50</sub>	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PC	Product category
PNEC	Predicted No Effect Concentration
PROC	Process Category
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds

### 16.3. Key literature references and sources for data

No data available

### 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters ( <i>Aerosol 1</i> )	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
Serious eye damage/eye irritation ( <i>Eye Irrit. 2</i> )	H319: Causes serious eye irritation.	
STOT-single exposure ( <i>STOT SE 3</i> )	H336: May cause drowsiness or dizziness.	

### 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H201	Explosive; mass explosion hazard.
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

**Revision date:** 19 Aug 2025

**Print date:** 20 Aug 2025

**Version:** 2

Page 18/18



## Paint Tech Evo white (plast) 500ml

### Hazard statements

H351	Suspected of causing cancer.
------	------------------------------

### Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

### 16.6. Training advice

No data available

### 16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

\* Data changed compared with the previous version.