

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7

Page 1/14



Mega Foam 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Mega Foam 500ml

Article No.:

T101001

UFI:

G9CF-AUG7-AJHC-N871

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Glass cleaner

Relevant identified uses:

Product Categories [PC]

PC 35: Washing and cleaning products

* 1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

E-mail: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02

Flame

Signal word: Danger

Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 2/14

Mega Foam 500ml

Supplemental hazard information: none

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.

Precautionary statements Storage

P403	Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional information:

Formation of explosive mixtures possible without adequate ventilation.
Cleaner (according to detergents guideline 648/2004/EC)

* 2.3. Other hazards

Other adverse effects:

The product does not meet the PBT/vPvB criteria.

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard. The wording of the listed hazard statements can be found in section 16.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
	Aliphatic hydrocarbons The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. Additional information: Ingredients according to detergents guideline 648/2004/EC	≥ 5 - < 15 Vol-%
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	butane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) ⚠ Danger Acute Toxicity Estimate ATE (oral) ≥ 5,000 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, gases) 658 ppmV ATE (inhalation, vapour) ≥ 50 mg/L	2.5 - < 10 Vol-%
CAS No.: 67-63-0 EC No.: 200-661-7 Index No.: 603-117-00-0 REACH No.: 01-2119457558-25	propan-2-ol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) ⚠⚠ Danger Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) > 20 mg/L	2.5 - < 10 Vol-%

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 3/14

Mega Foam 500ml

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21	propane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger Acute Toxicity Estimate ATE (oral) 5,840 mg/kg ATE (dermal) 13,900 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) ≥ 50 mg/L	2.5 - < 10 Vol-%
	non-ionic surfactants, perfumes The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP]. Additional information: Ingredients according to detergents guideline 648/2004/EC	< 5 Vol-%
CAS No.: 107-98-2 EC No.: 203-539-1 Index No.: 603-064-00-3 REACH No.: 01-2119457435-35	1-methoxypropan-2-ol Flam. Liq. 3 (H226), STOT SE 3 (H336) Warning Acute Toxicity Estimate ATE (oral) 4,016 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) 28.8 ppmV ATE (inhalation, vapour) 27.596 mg/L Additional information: Consists of: 1589-47-5 2-Methoxypropanol (>0.1-<0.3%)	1 - < 2.5 Vol-%
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	Isobutane (contains < 0.1% butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger Acute Toxicity Estimate ATE (oral) > 15,000 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, vapour) > 4,951 mg/L	0.1 - < 1 Vol-%
CAS No.: 1336-21-6 EC No.: 215-647-6 REACH No.: 01-2119982985-14	ammonia, aqueous solution Aquatic Chronic 3 (H412), Eye Dam. 1 (H318), STOT SE 3 (H335), Skin Corr. 1B (H314) Danger Specific concentration limit (SCL) STOT SE 3; H335: C ≥ 5% Acute Toxicity Estimate ATE (oral) 350 mg/kg ATE (dermal) ≥ 5,000 mg/kg ATE (inhalation, vapour) ≥ 50 mg/L Additional information: (24,5%)	0.1 - < 1 Vol-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

In general, the product is not irritating to skin.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7

Page 4/14



Mega Foam 500ml

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide, alcohol resistant foam

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray against a flame or on a glowing object. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B – Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 5/14

Mega Foam 500ml

7.3. Specific end use(s)

Recommendation:

No further relevant information available.

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	butane CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m ³)
MAK (AT)	butane CAS No.: 106-97-8 EC No.: 203-448-7	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	② 800 ppm (2,000 mg/m ³) ⑤ (max. 4x15 min./Schicht)
MAK (AT)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm (500 mg/m ³)
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	② 2,000 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m ³)
IOELV (EU)	1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	① 100 ppm (375 mg/m ³) ② 150 ppm (568 mg/m ³) ⑤ (may be absorbed through the skin)
MAK (AT)	1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	① 50 ppm (187 mg/m ³) ② 50 ppm (187 mg/m ³) ⑤ (Momentanwert, kann über die Haut aufgenommen werden) H
MAK (AT)	Isobutane (contains < 0.1% butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht Momentanwert)
MAK (AT)	Isobutane (contains < 0.1% butadiene (203-450-8)) CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m ³)

8.1.2. Biological limit values

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 6/14

Mega Foam 500ml

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	369 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	43.9 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	553.5 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	50.6 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	18.1 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	3.3 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, intermittent release

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 7/14

Mega Foam 500ml

Substance name	PNEC Value	① PNEC type
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	10 mg/L	① PNEC aquatic, freshwater
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	1 mg/L	① PNEC aquatic, marine water
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	100 mg/L	① PNEC sewage treatment plant
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	52.3 mg/kg	① PNEC sediment, freshwater
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	5.2 mg/kg	① PNEC sediment, marine water
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	4.49 mg/kg	① PNEC soil
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1	100 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety glasses or goggles (EN 166).

Skin protection:

Hand protection: Gloves / solvent resistant. Selection of glove material considering breakthrough times, permeation rates and degradation.

Glove material: The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

NBR (Nitrile rubber), Recommended material thickness: $\geq 0,5$ mm

Permeation time (maximum wear duration): For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

Body protection: Antistatic, chemical and oil resistant clothing and safety shoes are recommended. (EN1149; EN340&EN ISO 13688; EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter ABEK-P2

Other protection measures:

General protective and hygienic measures: Wash hands before breaks and after work. General ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 8/14

Mega Foam 500ml

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol

Colour: colourless

Odour: Alcohol

flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	not applicable		② Mixture is not polar/aprotic.
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	-44.5 °C		
Flash point	-97 °C		
Evaporation rate	No data available		
Auto-ignition temperature	365 °C		② butane
Upper/lower flammability or explosive limits	1.5 - 13.7 Vol-%		② butane - 1-methoxypropan-2-ol
Vapour pressure	23 hPa	20 °C	② Water
Vapour density	No data available		
Density	0.946 g/cm ³	20 °C	
Bulk density	not applicable		
Water solubility	completely miscible		
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		
flammability			② Easily flammable

* 9.2. Other information

Form: Aerosol

Auto-ignition temperature: The product is not self-igniting.

Organic solvents: 16,0 %

Water: 83,6 %

Solid content: 0,0 %

9.2.1. Information with regard to physical hazard classes

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7

Page 9/14



Mega Foam 500ml

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LD₅₀ oral: >2,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): >20 mg/L 6 h (Rat)
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
ATE (oral): 4,016 mg/kg
LD₅₀ oral: 4,016 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): 28.8 ppmV 4 h (Rat)
LC₅₀ Acute inhalation toxicity (vapour): 27.596 mg/L 6 h (Rat)

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7

Page 10/14



Mega Foam 500ml

SECTION 12: Ecological information

* 12.1. Toxicity

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LC₅₀ : >1,000 mg/L 4 d (fish)
LC₅₀ : 9,640 mg/L 4 d (fish, Pimephales promelas)
LC₅₀ : 9,714 mg/L 1 d (Daphnia magna)
EC₅₀ : >1,000 mg/L 2 d (crustaceans)
EC₅₀ : >100 mg/L (Algae/water plant, Bacteria)
EC₅₀ : >100 mg/L 2 d (crustaceans, Daphnia magna)
ErC₅₀ : >100 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)
ErC₅₀ : >100 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus)
LOEC : 1,000 mg/L (Alge)
LOEC : 1,000 mg/L (Algae/water plant, Algae)
LOEC : 1,000 mg/L
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
LC₅₀ : 6,812 mg/L 4 d (fish, Leuciscus idus)
EC₅₀ : 23,300 mg/L 2 d (crustaceans, Daphnia magna)
LC₅₀ : 6,812 mg/L 4 d (Leuciscus idus)
LC₅₀ : >1,000 mg/L 4 d (Oncorhynchus mykiss)
EC₅₀ : 23,300 mg/L 2 d (Daphnia magna)
EC₅₀ : >1,000 mg/L 2 d (Daphnia magna)

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Biodegradation : Yes, rapidly
Remark : Readily biodegradable (according to OECD criteria).
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
Biodegradation : Yes, rapidly

Biodegradation:

Not readily biodegradable.

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Log K_{OW} : 0.05
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
Log K_{OW} : -0.44

Bioconcentration factor (BCF):

No further relevant information available.

* 12.4. Mobility in soil

No further relevant information available.

12.5. Results of PBT and vPvB assessment

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Results of PBT and vPvB assessment : —
1-methoxypropan-2-ol CAS No.: 107-98-2 EC No.: 203-539-1
Results of PBT and vPvB assessment : —
Aliphatic hydrocarbons
Results of PBT and vPvB assessment : —

The product does not meet the PBT/vPvB criteria.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7

Page 11/14



Mega Foam 500ml

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

General information water hazard class 1 - slightly hazardous to water; Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
------	-----------

Waste treatment options




Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

Recommended cleaning agent: Water, if necessary with the addition of cleaning agents.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable
14.3. Transport hazard class(es)			
 2.1	No data available	 2.1	 2.1
14.4. Packing group			
		-	
14.5. Environmental hazards			
No data available	No data available	No data available	No data available
14.6. Special precautions for user			
Special Provisions: Attention: Gases Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D)	Special Provisions: Attention: Gases Classification code: 5F	Special Provisions: Attention: Gases Limited quantity (LQ): 1L Excepted Quantities (EQ): E0 EmS-No.: F-D,S-U Remark: Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity	Special Provisions: Attention: Gases

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7

Page 12/14



Mega Foam 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
		above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.	

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Seveso category P3a FLAMMABLE AEROSOLS

Quantity threshold (in tons) for use in lower class farms 150t

Quantity threshold (in tons) for use in upper-tier establishments 500t

Restrictions on use:

Regulation (EC) No 1907/2006 ANNEX XVII Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 151.6 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
2.3.	Other hazards
3.2.	Mixtures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 13/14

Mega Foam 500ml

8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
9.2.	Other information
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.4.	Mobility in soil
14.6.	Special precautions for user
15.3.	Additional information
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

Limit value / limit values updated: SI

* 16.2. Abbreviations and acronyms

AC	Article Category
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Standards Organisation
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PC	Product category
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
SCL	Specific concentration limit
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Revision date: 19 Aug 2025

Print date: 25 Aug 2025

Version: 7



Page 14/14

Mega Foam 500ml

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.