

### LTP22

# THE LIGHT WEIGHT AND HAND HELD TORCH SYSTEM

- · Automatic piezo ignition
- Trigger on/off function no waste of LP gas
- Operates in all positions
- Wide range of quick changeable burners
- · For disposable cartridges.
- Ergonomic light weight composite handle or sturdy heavy duty metal handle
- Provides a temperature of 2200° C



# **LOTPISTOLE ULTRAMAPP 2200**

#### **General Information**

Metaljet and Ultramapp gas form together the most powerful and efficient torch system on the market. A combination of modern combustion technology and unique gas mixture gives you a flame temperature of 2200°C. Sturdy metal handle with stainless steel high efficient cyclone burner 8707 for instant heat around the pipe. Heating, brazing and soldering works will be done with highest quality efficiency.

PLEASE NOTE:

Before using upside down, warm up 30 sec.

#### **Technical Information**

Working pressure: 2 bar For ultragas catridge (not included): 2206 Can be used with all burners. NO BURNER INCLUDED!

#### **Application and Use**

- 8702: Pin-point burner for small soft soldering jobs. Gives a precise and stable flame Burner diameter: 15mm Gas consumption, at 2 bar: 40g/h Effect, at 2 bar: 0,5kW Soft soldering at 2 bar: 10mm
- 8704: Standard burner for soft soldering and other small heating jobs. For soft soldering and other small heating jobs.
   Burner diameter: 16 m Gas consumption, at 2 bar: 90g/h Effect, at 2 bar: 1,2kW Soft soldering at 2 bar: 18mm
- 8706: Cyclone burner for brazing and soft soldering. Intensive and effective short flame that reaches around the pipe.
   Burner diameter: 14 mm Gas consumption, at 2 bar: 170g/h Effect, at 2 bar: 2,2 kW
   Soft soldering: 40 mm

Brazing at 2 bar: 18mm

• 8707: Cyclone burner for brazing and soft soldering. High efficient cyclone burner with

increased tip diameter.

Burner diameter: 16 mm

Gas consumption, at 2 bar: 230g/h

Effect, at 2 bar: 2,9kW Soft soldering: 40 mm Brazing at 2 bar:18mm

8708: Hot-air burner or shrinking and paint stripping. Powerful and wind stable hot-air

stream.

Burner diameter: 38mm Gas consumption, at 2 bar: 130g/h

Effect, at 2 bar: 1,7kW

8710: Soft flame burner or shrinking and heating jobs. Powerful and wind stable soft

flame.

Burner diameter: 24 mm Gas consumption, at 2 bar: 230g/h Effect, at 2 bar: 3,5 kW

Soft soldering at 2 bar: 22 mm

Copper bit: Made f copper with one pointed and one flat end. For use with burner 8702.

Article nr	Name	Content	Shelf Life	Catalog
Y902155	Lotpistole	1pc.	-	TOOLS
	Ultramapp 2200			
Y902210	Mapp Pure	640 ml	-	TOOLS
	Propylene			
Y908702	Pin-Point Burner	1pc.	-	TOOLS
Y908704	Standard Burner	1pc.	-	TOOLS
Y908706	Cyclon Burner	1pc.	-	TOOLS
Y908708	Hot-Air Burner	1pc.	-	TOOLS
Y908710	Soft Flame Burner	1pc.	-	TOOLS
Y908843	Copper Bit	1pc.	-	TOOLS

### Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

















