

UTS

ONE PRODUCT FOR CLEANING AND ETCHING

- · Powerful solvent cleaner and diluent
- Perfectly suitable for etching before glueing or using lacquers, etc.
- Creates a good adherence to most lacquers, such as powder coating and synthetic materials through etching
- Can be used as diluent for epoxys
- · Evaporates quickly



ULTRASOLV

General Information

ULTRASOLV is the ideal combination product for efficient cleaning and etching of surfaces. Due to its powerful formulation ULTRASOLV can be used as echting agent before glueing or using laquers. In addition ULTRASOLV is perfectly suitable as a diluent

for epoxys. ULTRASOLV also works as a fluid abrasive on various lacquers and synthetic materials. ULTRASOLV offers a strong cleaning performance and evaporates quickly.

Technical Information

Aggregate State: Liquid Colour: colourless Odour: characteristic Melting point: < -86 °C

Initial boiling point and boiling range: 78 - 80 $^{\circ}\text{C}$

Flash point: -7 °C

Upper/lower flammability or explosive limits: 1 - 11 $\,$

Vol-%

Vapour pressure: 10,5 kPa (20 °C) Density: 0,804 - 0,808 g/cm³ (20 °C) Partition coefficient: n-octanol/water: 0,3 Refractive index (20 °C): 1,3720 - 1,3820

Shelf life: 12 months

Application and Use

- Ideal for finishing of epoxys
- · Removes hardened polyurethane

 Fluid abrasive for hardened epoxys such as MORTAR FIX, lacquers etc.

			·	
Article nr	Name	Content	Shelf Life	Catalog
T689001	Ultrasolv 1I	11	see imprint + 36 months	CLEANERS AND
				DEGREASERS
T689005	Ultrasolv 5I	51	see imprint + 36 months	CLEANERS AND
				DEGREASERS

Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



