

RUSA

RUST EXTERMINATOR

- Chemically neutralizes rust.
- Leaves a tough, long term rust preventative coating.
- Seals, protects and prolongs the life of ferrous metals.
- Turns rusted area to a black protective finish.
- The protective barrier, upon curing, can be painted if desired.
- Can be overpainted.



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

RUSTCON AEROSOL

General Information

RUSTCON AEROSOL is an innovative new chemical formula that actually transforms

un-wanted rust into a tough, black-glass rust resistant polymer finish.

Technical Information

Type: polymeric, air cured coating
 Form: aerosol
 Colour: light brown
 Odour: characteristic
 Flash point: -42°C
 Boiling point: -24,8°C
 Auto-ignition temperature: 235°C

Lower explosion limit: 1,1 Vol%
 Upper explosion limit: 20,0 Vol%
 Vapour pressure (at 20°C): 5200 hPa
 Density (at 20°C): 0,797 g/cm³
 Kinematic viscosity (at 40°C): ≤ 20,5 mm²/s
 Store cool and dry
 Safety measures: consult the Safety Data Sheet

Application and Use

- Surface Preparation: Surfaces must be clean, dry and free of grease, dirt and oil. Remove loose rust and paint with coarse sand paper or wire brush.
- Shake RUSTCON AEROSOL well for at least one minute before using.
- Apply when work piece and can are at temperature of 8-25°C.
- Holding can 20 to 30 cm from the surface, spray a thin, even coating of RUSTCON AEROSOL onto the rusted metal. Spray 2-3 layers "wet in wet" without sagging.
- Let the layer convert and dry.
- Final application will dry to a black finish.
- Maybe painted after curing for approximately six hours.

Article nr	Name	Content	Shelf Life	Catalog
T180001	Rustcon 1l	1l	see imprint + 24 months	SURFACE PROTECTION AND TREATMENT
T180005	Rustcon 5l	5l	see imprint + 24 months	SURFACE PROTECTION AND TREATMENT
T181001	Rustcon Aerosol 500ml	500ml	see imprint + 36 months	SURFACE PROTECTION AND TREATMENT
Y390302	Glove GoGrip NI M	50 pcs.	-	HEALTH AND SAFETY
Y898001	Oil Tissues 40x40cm	100pcs.	-	TOOLS
Y899050	Cleaning Cloth small 2-ply	1 roll	-	TOOLS
Y899201	Wall Holder	1pc.	-	TOOLS

