

GFS

POWERFUL SPRAY-ADHESIVE FOR ALL- ROUND PURPOSES

- Easy to use, especially on large areas.
- Forms a strong bond.
- Shows fast adhesion.
- Temperature and moisture resistant.
- Has a high viscosity.



GLUE FIX SPRAY

General Information

GLUE FIX SPRAY is a multifunctional spray aerosol based on styrene-butadiene-rubber, resins and hydrocarbon solvents. GLUE FIX SPRAY gets its extraordinary performance through a combination of a special spray nozzle and the adhesives recipe. With the special nozzle it can be sprayed in a web-structure, which shows very good results even on rough surfaces. The GLUE FIX SPRAY nozzle does not only come with a special web-technology, but also with a 3 position valve

to always have the right amount of adhesive. This guarantees the most economical use of GLUE FIX SPRAY. The spray adhesive is unavoidable, where a brush or other application techniques cannot be used. GLUE FIX SPRAY can also be used on vertical surfaces, as it does not drip. It bonds a wide variety of materials such as wood, stone, rubber, canvas fabrics, cardboard, metal, paper, cork, foam etc.

Technical Information

Physical state: Aerosol
 Colour: According to product designation
 Odour: characteristic
 Initial boiling point and boiling range: -44.5 °C
 Flash point: -97 °C
 Auto-ignition temperature: > 200 °C
 Upper/lower flammability or explosive limits: 1.1 - 13 Vol-%
 Pressure (20°C): 4,5 Bar
 Vapour pressure: 8,300 hPa
 Spray rate: 3 position valve; high, medium, low (2 g/sec middle position)

Spray pattern: Thick Web Wires; Will not run off, even not on vertical surfaces.
 Odour: Solvents
 Viscosity (20°C): ≤ 20.5 mm²/s
 Drying time (20°C): Ca. 2 min. (two sides adhesion), 30 sec for foam
 Open time: Max.15 min.
 Temperature resistance: Max. 60°C
 Density (20°C): 0.71 g/cm³
 Application temperature: 10°C - 35°C
 Storage conditions: Cool (10°C - 20°C) and dry

Application and Use

- Use on room temperature and shake well before use.
- Before using GLUE FIX SPRAY on any surfaces, these should be clean, dry and free from grease.
- Spray GLUE FIX SPRAY onto the surface/object to be glued and press firmly together.
- For 2-way application, spray both surfaces and allow drying for 10 minutes, then press them into position.
- After usage of GLUE FIX SPRAY turn the aerosol upside-down and spray until only gas is coming out.
- Remove unintentional spots immediately before drying with white spirit or acetone cleaner, such as FAST CLEAN or POWER STRIP.
- On coloured surfaces always test in a concealed area first. Discoloration may occur.

Article nr	Name	Content	Shelf Life	Catalog
T101001	Mega Foam 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
T109005	Safe Clean Eco 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
T511002	Glue Fix Spray 500ml	500ml	see imprint + 24 months	ADHESIVES AND SEALANTS
Y870010	Fold Scraper KIT	1pc.	-	TOOLS



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

