

PEV

PREMIUM HIGH PERFORMANCE SPRAY PAINT

- Universal Use: Suitable for metallic, synthetic, and natural substrates
- Superior Coverage: High pigment content for excellent opacity
- Exceptional Adhesion: Bonds strongly to all surfaces
- No Drips or Runs: Prevents running and nosing
- Durable Resistance: Protects against chemicals, UV rays, and weathering
- Rust & Corrosion Protection: Shields metal surfaces effectively
- Elastic & Shock-Resistant: Excellent flexibility and impact resistance
- Perfect Edge Coverage: Ensures full coverage along edges
- Fast Drying: Quick-dry formula for efficient further processing
- Multiple Finishes: Silk matt, glossy, or transparent
- Versatile Coating System: Ideal as primer, intermediate, and top coat
- For Interior & Exterior Use: Long-lasting performance anywhere
- Color Options: 6 RAL colors, plus white plast, black matt, black glossy, wheel alu, and transparent
- Enhanced Applicator: Adjustable nozzle, colored donuts, and transparent lids



Notice

All information and illustrations are provided to the best of our knowledge and belief. It is the responsibility of the consumer to determine the suitability of each product for its particular application. We give no guarantee with regard to the completeness or accuracy of the information and disclaim any liability for the use of the product. Liability is limited to the use specified in the standard conditions of sale for this product. In no event shall we be liable for any damages or consequential damages arising out of the sale, resale, use or misuse of the product.

PAINT TECH EVO

General Information

PAINT TECH EVO is a professional high-performance spray paint, available in six RAL colors and additional shades. It is ideal for use as a primer, intermediate, or top coat and adheres exceptionally well to all metallic, synthetic, and natural substrates—without running. PAINT TECH EVO offers optimal coverage and high elasticity thanks to its high-quality color pigments. It provides excellent corrosion protection, high impact and

shock resistance, and very good edge coverage. Suitable for indoor and outdoor use, the spray paint is highly resistant to chemicals, UV rays, and weathering. PAINT TECH EVO dries quickly for efficient further processing and gives the surface a silky matt finish. The adjustable nozzle allows for precise dosing and adaptation to different applications. COLORED DONUTS make quick identification of colors easy.

Technical Information

Form: Aerosol
 Base: modified synthetic resin
 RAL Colors: grey RAL 7012 / anthracite RAL 7024 / black RAL 9005 / white RAL 9010 / red RAL 3020 / orange RAL 2011
 Additional Colors: white plast, black matt, black glossy, wheel alu, transparent lacquer
 Appearance: silk matt, glossy, transparent
 Odor: solvent-like
 Initial boiling point: < 0°C
 Flash point: < 0°C

Lower explosion limit: 1.2 vol%
 Upper explosion limit: 26.2 Vol%
 Auto-ignition temperature: > 300°C
 Density: 0.8 g/cm³
 Temperature resistance: 110°C
 Dust-dry/grip strength: 5 - 10 minutes
 Deep drying: 20 - 60 minutes (depending on layer thickness)
 Resistance: not resistant to petrol and solvents containing acetone
 Flammability: Highly flammable

Application and Use

- PAINT TECH EVO: Refinement, reconditioning, touch-up and repair work. For all substrates such as metal and non-ferrous metals, plastics (including ABS, PVC, PP, PE), textiles, wood, glass, ceramics, stone, concrete
- INDUSTRY: - windows - railings - gates - sheet steel constructions - appliances - containers - gutters - radiators - painted components - industrial machinery - cranes - transport racks.
- AUTOMOBILE: - spoilers - mirror covers - radiator grilles - bumpers - trim strips - dashboards - cladding and body
- parts for trucks, cars, motorcycles, boats, agricultural and construction machinery, winter service equipment
- Spray Nozzle - Key Features: Front nozzle: Adjustable vertically and horizontally for precise spray direction. Rear control: Vertical adjustment of material output, stepless from "+" (maximum flow/wide fan) to "-" (minimum flow/narrow fan or nearly round jet).
- USE: see label on the can for the right use

Article nr	Name	Content	Shelf Life	Catalog
T120202	Paint Tech Evo pale grey 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120213	Paint Tech Evo anthracite 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120222	Paint Tech Evo black 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120232	Paint Tech Evo white 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120242	Paint Tech Evo red 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120252	Paint Tech Evo white (plast) 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120262	Paint Tech Evo black matt 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120272	Paint Tech Evo black glossy 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120282	Paint Tech Evo Wheel Alu 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120283	Paint Tech Evo transparent 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T120289	Paint Tech Evo municipal-orange 500ml	500ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT

