TECH-MASTERS Trading GmbH
Perfektastraße 55, A-1230 Wien
Tel: +43 (0)1 / 867 29 07
office@tech-masters.com
www.tech-masters.eu

PTSR

PAINT TECH SPOT REPAIR

THINNER FOR PERFECT BLENDING

- Seamless blending of old and new paint – for invisible transitions
- Suitable for fresh clearcoat areas and overlapping wet spots
- Specially balanced formula with high-quality thinners – ensures consistent results
- Achieves professional, flawless finishes quickly and efficiently



General Information

PAINT TECH SPOT REPAIR is the ideal solution for seamlessly blending old and new paint on clear-coated bodywork, including areas with fresh clearcoat or overlapping wet spots after using PAINT TECH EVO. Its specially balanced formula and high-quality thinners ensure smooth, invisible transitions, making sanding and polishing easier, saving time, and guaranteeing perfect color matching. Essential for achieving professional, flawless finishes quickly and efficiently.

Technical Information

Form: Aerosol
Appearance: Clear
Base: mixture of solvents
Odor: solvent-like
Organic Solvents: 100%
Density (20°C): 0.75 g/cm³
EU VOC: 751,4 g/l

Flammability: Extremely flammable
Lower explosion limit: 3.3 vol%
Upper explosion limit: 26.2 Vol%
MHD: 48M
Before use, shake the aerosol
Best processing temperature 15 to 25°C
The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Application and Use

- APPLICATION:
- Apply to repaired areas on clear-coated surfaces to seamlessly blend old and new paint
- PAINT TECH SPOT REPAIR applied wet in wet
- USE:
- Clean the surface thoroughly with Safe Clean/Clean Spray (allow the surface to air) and DRY CLOTH, to remove dust, grease, dirt, oil, and other contaminants
- While the clearcoat is still fresh, apply a thin layer of PAINT TECH SPOT REPAIR to the transition areas between the fresh PAINT TECH EVO transparent
- and the existing clearcoat to ensure a seamless transition between old and new layers
- Apply additional layers on the transition areas as needed to achieve an even coating
- After the clearcoat has fully cured, treat the area with CARE & PROTECT POLISH (silicone-free) to achieve a perfectly clean and smooth finish

Article nr	Name	Content	Shelf Life	Catalog
T120288	Paint Tech Spot Repair 400ml	400ml	see imprint + 48 months	SURFACE PROTECTION AND TREATMENT
T172001	Care & Protect Polish 1l	1l	see imprint + 24 months	SURFACE PROTECTION AND TREATMENT
T204001	Safe Clean Aerosol 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
T471001	Clean Spray 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
T899125	Dry Cloth	125pcs./Box	-	TOOLS
Y390303	Glove GoGrip NI L	50 pcs.	-	HEALTH AND SAFETY








Notice

All information and illustrations are provided to the best of our knowledge and belief. It is the responsibility of the consumer to determine the suitability of each product for its particular application. We give no guarantee with regard to the completeness or accuracy of the information and disclaim any liability for the use of the product. Liability is limited to the use specified in the standard conditions of sale for this product. In no event shall we be liable for any damages or consequential damages arising out of the sale, resale, use or misuse of the product.