TECH-MASTERS Trading GmbH
Perfektastraße 55, A-1230 Wien
Tel: +43 (0)1 / 867 29 07
office@tech-masters.com
www.tech-masters.eu

BLT

BELT STOP

STOPS SLIPPING RELIABLY

- Can be used on all types of flat-ribbed, V-belts and conveyor belts.
- Reduces slippage.
- Cleans and conditions.
- Highly adhesive.
- Extends belt life.
- Not harmful to canvas, leather or rubber.
- NSF approved for food industry



General Information

BELT STOP is a clear and tacky lubricant, that eliminates irritating belt squeal and recovering of lost traction and belt slippage.
BELT STOP is used to increase the transcription of drivebelts and transport belts.
BELT STOP puts a stop to cracks, squeaking and repells dirt, dust and grease.

BELT STOP is suitable for all kinds of belts, like, types of flat-ribbed, V-belts and conveyor belts, despite of size or transmission speed.
BELT STOP is safe to use on leather, rubber, canvas, silicones and all kinds of materials of belts.

Technical Information



Base: Solvents, highly tacky lubricants, polymers
Propellant: Carbondioxide
Physical state: Aerosol
Colour: According to product designation
Odour: characteristic
Initial boiling point and boiling range: -56.6 °C
Auto-ignition temperature: 285 °C



Upper/lower flammability or explosive limits: 1.4 – 13 Vol-%
Flash point: -35 °C
Vapour pressure: 573 hPa
Density: 0.685 g/cm³
Pressure(20°C): 4 Bar
Spray pattern: Mist, tacky coating
Color: Colorless

Application and Use

- Recomended application temperature for BELT STOP is approximately 25°C.
- For best results shake the can well before use.
- BELT STOP should be spread while the engine is idling. Spray BELT STOP lightly on inner working surface of belt.
- With BELT STOP only a uniform thin coat is sufficient.
- After application allow the belt to run for several minutes and avoid excessive amount.
- BELT STOP can be used in all industries, for example production industry, food industry, automotive industry etc...
- Applications: forklifts, cooler trucks, floor cleaning machines, drive belts, conveyor belts,...

Article nr	Name	Content	Shelf Life	Catalog
T132501	Belt Stop NSF 500ml	500ml	see imprint + 36 months	LUBRICANTS
Y390303	Glove GoGrip NI L	50 pcs.	-	HEALTH AND SAFETY

Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.