

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 1/14



Silico H1 500ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Silico H1 500ml

Article No.:

T201100

UFI:

HKWM-U26U-JT0W-FJDN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Lubricating agent

1.3. Details of the supplier of the safety data sheet

Supplier:

KANDO Service GmbH

Hartleitnerstraße 3

4653 Eberstälzell

Austria

Telephone: +43 (0) 7241 213 79

Email: msds@kando.eu

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), Stubenring 6, 1010 Wien, 24h: 01 406 43 43, Montag - Freitag: 8 bis 16 Uhr, Tel.: 01 406 68 98 (keine medizinische Auskunft) (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (<i>Aerosol 1</i>)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (<i>Aquatic Chronic 3</i>)	H412: Harmful to aquatic life with long lasting effects.	

* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5



Page 2/14

Silico H1 500ml

Hazard components for labelling:

pentane

Hazard statements for physical hazards

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Hazard statements for health hazards

H336	May cause drowsiness or dizziness.
------	------------------------------------

Hazard statements for environmental hazards

H412	Harmful to aquatic life with long lasting effects.
------	--

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing and eye protection/face protection.

Precautionary statements Response

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER if you feel unwell.

Precautionary statements Storage

P403	Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements Disposal

P501	Dispose of contents/container to an appropriate recycling or disposal facility.
------	---

Additional information:

Formation of explosive mixtures possible without adequate ventilation.

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Active ingredient mixture with propellant gas

Additional information:

Aerosols and containers fitted with a solid nebuliser containing substances or mixtures classified as hazardous by aspiration must not be labelled for this hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5



Page 3/14

Silico H1 500ml

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 106-97-8 EC No.: 203-448-7 Index No.: 601-004-00-0 REACH No.: 01-2119474691-32	Butane (with < 0,1 % butadiene (203-450-8)) Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger Acute Toxicity Estimate ATE (inhalation, gases) > 800,000 ppmV ATE (inhalation, vapour) 658 mg/L	50 - < 75 %
CAS No.: 74-98-6 EC No.: 200-827-9 Index No.: 601-003-00-5 REACH No.: 01-2119486944-21	propane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger Acute Toxicity Estimate ATE (oral) 5,840 mg/kg ATE (dermal) 13,900 mg/kg ATE (inhalation, gases) > 25 ppmV ATE (inhalation, vapour) ≥ 50 mg/L	10 - < 25 %
CAS No.: 109-66-0 EC No.: 203-692-4 Index No.: 601-006-00-1 REACH No.: 01-2119459286-30	pentane Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066 Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, gases) > 20 ppmV ATE (inhalation, vapour) > 25.3 mg/L ----- Additional information: EUH066	2.5 - < 10 %
CAS No.: 75-28-5 EC No.: 200-857-2 REACH No.: 01-2119485395-27	Isobutane Flam. Gas 1A (H220), Press. Gas (Comp.) (H280) Danger Acute Toxicity Estimate ATE (inhalation, vapour) 1,237 mg/L	2.5 - < 10 %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Fresh air supply, consult a doctor in case of complaints.

In case of skin contact:

In general, the product is not irritating to skin.

After eye contact:

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist

Following ingestion:

Do not induce vomiting, seek medical help immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water mist, Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam

Unsuitable extinguishing media:

Water in full jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 4/14



Silico H1 500ml

5.2. Special hazards arising from the substance or mixture

No further relevant information available.

5.3. Advice for firefighters

Special protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Wear protective equipment. Keep unprotected persons away.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of spillage into water or sewage system, inform the competent authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Do not wash away with water or aqueous detergents.

Other information:

Provide adequate ventilation.

6.4. Reference to other sections

See section 7 for further information on safe handling.

For further information on personal protective equipment: see section 8.

For further information on disposal: see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Ensure good ventilation/extraction at the workplace.

Fire prevent measures:

Do not spray on naked flames or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Container is under pressure. Protect from sunlight and temperatures above 50°C (e.g. from incandescent lamps). Do not open by force or burn even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Store in a cool place. The official regulations for the storage of pressurised gas packages must be observed.

Hints on storage assembly:

The official regulations for the storage of pressurised gas packages must be observed.

Storage class (TRGS 510, Germany): 2B – Aerosol dispensers and lighters

Further information on storage conditions:

Store in a cool, dry place in well-sealed containers. Protect from heat and direct sunlight.

* **7.3. Specific end use(s)**

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 5/14



Silico H1 500ml

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	① 800 ppm (1,900 mg/m ³)
MAK (AT)	Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert) 60(Mow); 3x
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	② 2,000 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert) 60(Mow); 3x
MAK (AT)	propane CAS No.: 74-98-6 EC No.: 200-827-9	① 1,000 ppm (1,800 mg/m ³)
IOELV (EU)	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 1,000 ppm (3,000 mg/m ³)
MAK (AT) from 1 Jan 2026	pentane CAS No.: 109-66-0 EC No.: 203-692-4	② 1,200 ppm (3,600 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert) 60(Mow); 3x
MAK (AT) from 1 Jan 2026	pentane CAS No.: 109-66-0 EC No.: 203-692-4	① 600 ppm (1,800 mg/m ³)
MAK (AT)	Isobutane CAS No.: 75-28-5 EC No.: 200-857-2	② 1,600 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./SchichtMomentanwert) 60(Mow); 3x
MAK (AT)	Isobutane CAS No.: 75-28-5 EC No.: 200-857-2	① 800 ppm (1,900 mg/m ³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3,000 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	643 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	432 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5



Page 6/14

Silico H1 500ml

Substance name	DNEL value	① DNEL type ② Exposure route
pentane CAS No.: 109-66-0 EC No.: 203-692-4	214 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.23 mg/L	① PNEC aquatic, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	3.6 mg/L	① PNEC sewage treatment plant
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg bw/ day	① PNEC sediment, freshwater
pentane CAS No.: 109-66-0 EC No.: 203-692-4	1.2 mg/kg	① PNEC sediment, marine water
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.55 mg/kg	① PNEC soil
pentane CAS No.: 109-66-0 EC No.: 203-692-4	0.88 mg/L	① PNEC aquatic, intermittent release

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No further details. See section 7.

8.2.2. Personal protection equipment



Eye/face protection:

Safety goggles (EN-166)

Skin protection:

Hand protection:

Wear gloves for protection against chemicals according to EN 374.

Gloves / solvent resistant

Selection of glove material considering breakthrough times, permeation rates and degradation.

Glove material:

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use. NBR (Nitrile rubber)

Recommended material thickness: $\geq 0,5$ mm

Permeation time (maximum wear duration):

For continuous contact we recommend gloves with a breakthrough time of at least 240 minutes, with the preference for a breakthrough time greater than 480 minutes. For short term or splash protection we recommend the same. We are aware that suitable gloves offering this protection are not available. In this case, a shorter breakthrough time is permissible, provided the procedures for maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance the gloves give against a chemical substance, as this depends on the exact composition of the material of the gloves. The exact breakthrough time should be checked with the glove manufacturer and adhered to.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5



Page 7/14

Silico H1 500ml

Body protection:

Use protective suit. (EN-13034/6)

It is recommended to wear antistatic, chemical and oil-resistant clothing and safety shoes that completely cover the skin. (EN1149; EN340&EN ISO 13688; EN13034-6).

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Filter A2/P2

Other protection measures:

General protective and hygienic measures: Keep away from food, drink and animal feed. Wash hands before breaks and after work. Do not inhale gases/vapours/aerosols. General ventilation.

8.2.3. Environmental exposure controls

Use a suitable container to prevent environmental pollution.

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Form: Aerosol

Colour: According to product designation

Odour: characteristic

flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		② Mixture is not polar/aprotic.
Initial boiling point and boiling range	-44.5 °C		
Flash point	-97 °C		
Evaporation rate	<i>No data available</i>		
Auto-ignition temperature	285 °C		
Upper/lower flammability or explosive limits	1.4 - 10.9 Vol-%		
Vapour pressure	3,500 hPa	20 °C	② 3,0 Bar; <8000 hPa (50°C)
Density	0.585 g/cm ³	20 °C	
Water solubility	Immiscible		

* 9.2. Other information

The product is not self-igniting. The product is not explosive, but the formation of explosive vapour/air mixtures is possible. formation of explosive vapour/air mixtures is possible.

Organic solvents: 91,0 %

Solid content: 0,0 %

9.2.1. Information with regard to physical hazard classes

Aerosols:

Extremely flammable aerosol. Pressurized container: May burst if heated.

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

Thermal decomposition / Conditions to avoid: No decomposition when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 8/14



Silico H1 500ml

10.6. Hazardous decomposition products

No dangerous decomposition products known.

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Butane (with < 0,1 % butadiene (203-450-8))	CAS No.: 106-97-8	EC No.: 203-448-7
LC₅₀ Acute inhalation toxicity (gas): >800,000 ppmV (Rat)		
LC₅₀ Acute inhalation toxicity (vapour): 658 mg/L 4 h (Rat)		
propane	CAS No.: 74-98-6	EC No.: 200-827-9
LD₅₀ oral: 5,840 mg/kg (Rat)		
LD₅₀ dermal: 13,900 mg/kg (Rabbit)		
LC₅₀ Acute inhalation toxicity (gas): >25 ppmV 4 h (Rat)		
LC₅₀ Acute inhalation toxicity (vapour): ≥50 mg/L 4 h (Rat)		
pentane	CAS No.: 109-66-0	EC No.: 203-692-4
LD₅₀ oral: >5,000 mg/kg (Rat)		
LD₅₀ dermal: >2,000 mg/kg (Rat)		
LC₅₀ Acute inhalation toxicity (gas): >20 ppmV 4 h (rat)		
LC₅₀ Acute inhalation toxicity (vapour): >25.3 mg/L 4 h (Rat) OECD 403		
Isobutane	CAS No.: 75-28-5	EC No.: 200-857-2
LC₅₀ Acute inhalation toxicity (vapour): 1,237 mg/L (Mouse)		

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties:

None of the ingredients are included.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 9/14



Silico H1 500ml

SECTION 12: Ecological information

* 12.1. Toxicity

Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7

LC₅₀: 24.11 mg/L 4 d (fish) QSAR

LC₅₀: 14.22 mg/L 2 d (crustaceans) QSAR

LC₅₀: 24 mg/L 4 d (Pisces (generic)) ECOSAR QSAR

EC₅₀: 7.7 mg/L 4 d (Algae (generic)) ECOSAR v1.00 QSAR

propane CAS No.: 74-98-6 EC No.: 200-827-9

LC₅₀: 9,640 mg/L 4 d (fish, Pimephales promelas)

LC₅₀: 0.41 mg/L 4 d (fish, Oncorhynchus mykiss)

LC₅₀: 49.9 mg/L 4 d (fish)

EC₅₀: >100 mg/L (Algae/water plant, Bacteria)

EC₅₀: 0.17 mg/L 3 d (Algae/water plant, Selenastrum capricornutum)

EC₅₀: 69.43 mg/L 2 d (crustaceans, Daphnia) Calculation with the ECOSAR programme v1.00.

NOEC: 0.017 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

ErC₅₀: 19.37 mg/L 4 d (Algae/water plant, Algae) Calculation with the ECOSAR programme v1.00.

LOEC: 1,000 mg/L (Algae/water plant, Algae)

LOEC: 1,000 mg/L (Algae/water plant, Alge)

IC₅₀: 11.3 mg/L 3 d (Algae/water plant)

LOEC: 1,000 mg/L

pentane CAS No.: 109-66-0 EC No.: 203-692-4

LC₅₀: 4.26 mg/L 4 d (fish, Oncorhynchus mykiss)

EC₅₀: 10.7 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

EC₅₀: 2.7 mg/L 2 d (crustaceans, Daphnia magna)

NOEC: 7.51 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

NOEC: 7.51 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

EC₅₀: 10.7 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)

NOEC: 7.51 mg/L 3 d (Pseudokirchneriella subcapitata)

LC₅₀: 4.26 mg/L 4 d (Oncorhynchus mykiss)

LC₅₀: 4.26 mg/L 4 d (fish)

Isobutane CAS No.: 75-28-5 EC No.: 200-857-2

LC₅₀: 91.42 mg/L 4 d (fish)

EC₅₀: 69.43 mg/L 2 d (crustaceans, Daphnia sp.)

ErC₅₀: 19.37 mg/L 4 d (Algae/water plant)

* 12.2. Persistence and degradability

Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7

Biodegradation: Yes, rapidly

propane CAS No.: 74-98-6 EC No.: 200-827-9

Biodegradation: Yes, rapidly

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Biodegradation: Yes, rapidly

Biodegradation:

Not readily biodegradable.

* 12.3. Bioaccumulative potential

Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7

Log K_{OW}: 2.89

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 10/14



Silico H1 500ml

propane CAS No.: 74-98-6 EC No.: 200-827-9

Log K_{OW}: 1.09

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Log K_{OW}: 3.39

Isobutane CAS No.: 75-28-5 EC No.: 200-857-2

Log K_{OW}: 1.09

* 12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Butane (with < 0,1 % butadiene (203-450-8)) CAS No.: 106-97-8 EC No.: 203-448-7

Results of PBT and vPvB assessment: —

propane CAS No.: 74-98-6 EC No.: 200-827-9

Results of PBT and vPvB assessment: —

pentane CAS No.: 109-66-0 EC No.: 203-692-4

Results of PBT and vPvB assessment: —

Isobutane CAS No.: 75-28-5 EC No.: 200-857-2

Results of PBT and vPvB assessment: —

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

* 12.7. Other adverse effects

water hazard class 2: obviously hazardous to water, VOC value: 532,2 g/l (EU)

Harmful to fish. Do not allow to enter into surface water or drains. Drinking water hazard even when small quantities leak into the subsoil. Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Must not be disposed of together with household waste. Do not allow to enter into surface water or drains.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Directive 2008/98/EC (Waste Framework Directive)

HP 3 Flammable

HP 14 Ecotoxic

Waste treatment options

Appropriate disposal / Package:

Uncleaned packaging: Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
1950	1950	1950	1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable
14.3. Transport hazard class(es)			
 2.1	 2.1	 2.1	 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 11/14



Silico H1 500ml

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.4. Packing group			
		-	
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Tunnel restriction code: (D) Remark: Attention: Gases Transport category 2	Limited quantity (LQ): 1 L Excepted Quantities (EQ): E0 Classification code: 5F Remark: Attention: Gases	Limited quantity (LQ): Siehe SV277 Excepted Quantities (EQ): E0 EmS-No.: F-D, S-U Remark: Attention: Gases Stowage Code: SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.	Limited quantity (LQ): Y203 Excepted Quantities (EQ): E0 Remark: Attention: Gases On passenger aircraft/rail: 75kg On cargo aircraft only: 150kg

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Authorisations:

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients are included.

Restrictions on use:

Quantity threshold (in tons) for use in lower class farms 150t

Quantity threshold (in tons) for use in upper-tier establishments 500t

Regulation (EC) No 1907/2006 ANNEX XVII: Restriction conditions: 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II: None of the ingredients are included.

Regulation (EU) 2019/1148

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5



Page 12/14

Silico H1 500ml

Annex I - RESTRICTED EXPORT SUBSTANCES FOR EXPLOSIVES (upper concentration limit for a permit pursuant to Article 5(3)): None of the ingredients are included.

Annex II - EXPLOSIVES REPORTABLE FOR EXPLOSIVES: None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors: None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade in drug precursors between the Community and third countries: None of the ingredients are included.

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P3a 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids

Named dangerous substances:

- Liquefied flammable gases, Category 1 or 2 (including liquefied petroleum gas) and natural gas

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compound (VOC) content: 532.2 g/L

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

* 16.1. Indication of changes

2.2.	Label elements
7.3.	Specific end use(s)
8.1.	Control parameters
9.1.	Information on basic physical and chemical properties
9.2.	Other information
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.2.	Persistence and degradability
12.3.	Bioaccumulative potential
12.4.	Mobility in soil
12.7.	Other adverse effects
14.6.	Special precautions for user
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

* 16.2. Abbreviations and acronyms

AC	Article Category
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
AVV	Waste Shipment Ordinance (DE)
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DNEL	derived no-effect level
EAK	European Waste Catalogue
EC ₅₀	Effective Concentration 50%
EG	European Community
EN	European Standard
ES	Exposure scenario

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5



Page 13/14

Silico H1 500ml

EU	European Union
EWC	European Waste Catalogue
IC ₅₀	Inhibition Concentration 50 %
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Standards Organisation
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PNEC	Predicted No Effect Concentration
QSAR	Quantitative Structure-Activity Relationship
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
Tox.	Toxicity
TRGS	Technische Regeln für Gefahrstoffe
UFI	Unique Formula Identifier
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
aerosol dispensers and lighters (Aerosol 1)	H222; H229: Extremely flammable aerosol. Pressurised container: May burst if heated.	
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH), (EU) 2020/878

Date of creation: 1 Feb 2023

Revised on: 7 Sept 2026

Version: 6, replaces version 5

Page 14/14



Silico H1 500ml

16.7. Additional information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-mentioned supplier nor its subsidiaries assume any liability with regard to the correctness or completeness of the information provided. A final determination of the suitability of individual materials is the sole responsibility of the user. All materials may involve unknown risks and should be used with caution. While certain risks are described herein, we cannot guarantee that these are the only possible risks.

* Data changed compared with the previous version.