

GFS

POWERFUL SPRAY-ADHESIVE FOR ALL- ROUND PURPOSES

- Easy to use, especially on large areas
- Forms a strong bond
- Shows fast adhesion
- Clean to use
- Temperature and moisture resistant
- Low viscosity spray glue
- Coverage is approx. 1.4 m² / 500ml
- Bonds a wide variety of materials as:
- wood, stone, rubber, canvas fabrics,
- cardboard, metal, paper, cork, foam etc.



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

GLUE FIX SPRAY

General Information

GLUE FIX SPRAY is a multifunctional spray adhesive based on styrene-butadiene rubber, resins and hydrocarbon solvents. Its specially designed nozzle produces a web-like spray pattern, providing excellent bonding results even on rough and uneven surfaces. The 3-Pos. valve (high, med. and low) allows the adhesive output to be adjusted to the specific

application, ensuring economical and controlled use. The web-like spray pattern also allows application on vertical surfaces without dripping or running off. GLUE FIX SPRAY provides a strong, fast and moisture-resistant bond and is clean and easy to use. Its low-viscosity formulation enables an even application.

Technical Information

Physical state: Aerosol
 Colour: White liquid
 Odour: characteristic / Solvents
 Auto-ignition temperature: > 200 °C
 Upper/low. flammability/explosive limits: 1.1 - 13Vol-%
 Pressure (20°C): 4 Bar
 Vapour pressure: 8,300 hPa
 3 position valve: high, medium, low (2 g/sec mid pos.)
 Spray pattern: Mist, low viscosity gives a thin glue layer

Viscosity (20°C): ≤ 20.5 mm²/s
 Drying time (20°C): ca. 2 min. (2-sides adhesion), 30 sec for foam
 Open time: Max. 5 min.
 Temperature resistance: Max. 80°C
 Density (20°C): 0.7 g/ml
 Application temperature: 10°C - 35°C
 Storage conditions: Cool (10°C - 20°C) and dry
 Shelf Life: 24 Months

Application and Use

- Use at room temperature.
- Shake well before use.
- Surfaces must be
- clean, dry and free from grease.
- Remove adhesive spots immediately, before drying, with white spirit or an acetone-based,
- cleaner such as FAST CLEAN or POWER STRIP.
- On coloured surfaces, test on a concealed area first. Discoloration may occur.
- Spray onto the surface/object
- to be glued and press firmly together.
- For two-sided application, spray both surfaces, allow to dry for 5 minutes, then press firmly together.
- After use, turn the aerosol upside down and spray until only gas comes out to clean the spray valve.
- Keep away from heat, sparks, open flames and hot surfaces. No smoking.
- Pressurized container: Do not pierce or burn, even after use.
- Avoid breathing the spray, wear protective gloves and eye protection.
- Use only outdoors or in a well-ventilated area.

Article nr	Name	Content	Shelf Life	Catalog
T101001	Mega Foam 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
T109005	Safe Clean Eco 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
T511002	Glue Fix Spray 500ml	500ml	see imprint + 24 months	ADHESIVES AND SEALANTS
T899125	Dry Cloth	125pcs./Box	-	TOOLS
Y390303	Glove GoGrip NI L	50 pcs.	-	HEALTH AND SAFETY
Y870010	Fold Scraper KIT	1pc.	-	TOOLS

