TECH-MASTERS Trading GmbH
Perfektastraße 55, A-1230 Wien
Tel: +43 (0)1 / 867 29 07
office@tech-masters.com
www.tech-masters.eu

POS

POWER STRIP

HIGH PERFORMANCE PAINT STRIPPER SPRAY

- No more sanding, brushing and cutting
- Effectively removes paints, varnish, polyurethane, glue, sealings,...
- Can be used on various material like wood, metal, masonry,...
- Tixotropic - does not drip
- Ideal for vertical surfaces
- Works quick and is safe for users



General Information

POWER STRIP is a powerful high-performance strip spray for the removal of paints, varnishes, polyurethane and many more. By using POWER STRIP there is no need for sanding, brushing or cutting anymore.

Due to its special formulation, POWER STRIP can safely be used on various material like metal, masonry, glass, wood, stone,... POWER STRIP has a non-dripping tixotropic appearance which makes it ideal for the use on vertical surfaces.

Technical Information

Form: aerosol
Base: solvent mixture based on methylal, dioxolane, ketones, surfactants and paraffinic wax
Propellant: propane
Colour: translucent white
Odour: characteristic
Boiling point: -44,5°C
Flash point: -97°C

Auto-ignition temperature: 235°C
Lower explosion limit: 0,7 Vol%
Upper explosion limit: 19,9 Vol%
Density (at 20°C): 0,79 g/cm³
Water solubility: immiscible
Delivery rate (at 20°C): 2,4 g/sec
Application temperature: 10°C - 35°C
Storage: cool (10 - 20°C) and dry

Application and Use

- USE:
  - Shake can well before use.
  - Keep spray distance at 20-30cm and spray the area to be treated.
  - Wait approx. 25 minutes for paint or varnish to blister.
  - Remove the blister and then apply a second coat. Leave for approx. 20 minutes.
  - Remove blistered or softened paint/varnish with a stripping knife. Use a shavehook or old nylon toothbrush in difficult areas.
  - Repeat the process if necessary.
  - Remove traces of stubbon or ingrained paint by applying a final light coat and rubbing with a wire tool.
  - Scrub down with liquid detergent in cold water (use white spirit on fine woods to avoid raising the grain).
  - Allow to dry thoroughly. Rub down with either fine sandpaper or wire wool.
- APPLICATION:
  - For the removal of paints, undercoating
  - Can be used for stickers on parts, old packaging on various metal
  - Also removes hardened oils and carbon deposit on valve seats, cylinders and other engine parts
  - Strips of varnish, resin, paint, bitumen, graffiti on panels, windows, walls, boats, road builing tools, etc.

Article nr	Name	Content	Shelf Life	Catalog
T495001	Power Strip 500ml	500ml	see imprint + 36 months	CLEANERS AND DEGREASERS
Y390303	Glove GoGrip NI L	50 pcs.	-	HEALTH AND SAFETY
Y899050	Cleaning Cloth small 2-ply	1 roll	-	TOOLS



Notice

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.