

## NSL

### PAINTABLE SEALING CEMENT

- Can be applied on both dry and wet surfaces.
- Does not sag - does not string out.
- Fast skin cure.
- Does not contain silicones - can be painted immediately.
- Can be mixed with paint.
- Remains flexible - does not tear.
- Bonds to metal, glass, ceramics, wood, painted surfaces and most synthetic materials.
- Easy to apply, even on vertical surfaces.
- Can be applied between 5°C and 40°C.
- Perfect U.V. resistance.
- Contains no acids, thus no corrosion to metals.
- Available in two colors: clear and white.



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

## NOVASEAL

### GENERAL INFORMATION

NOVASEAL is a 1-component, high quality sealer based on liquid rubber, and packed in a standard cartridge. The product is

universally suitable for practically all building materials in both horizontal or vertical applications. After curing, the material stays flexible.

### TECHNICAL INFORMATION AND PACKAGING

Viscosity: soft-thixotropic.  
 Working time: 15 minutes.  
 Tensile strength: 1,5 N/mm<sup>2</sup>.  
 Elongation: 600%.  
 Weight/liter: 1,04 kg/liter.  
 Temp. of surface by application:  
 +5°C up to +40°C.  
 Temp. resistance after curing:

-25°C up to +100°C.  
 UV-resistance: excellent.  
 Water resistance: excellent.  
 Curing: 0,75 mm / 24 hours.

Shelf life: 12 months, keep dry, cool and frost-proof.  
 Safety measures: consult the Safety Data Sheet.

### APPLICATION AND USE

- Sealing of all substrates in:
  - automotive
  - airconditioning
  - electrical
- building and construction
- sanitary installations
- Novaseal bonds to: glass, metal, ceramics, wood, painted surfaces and synthetic materials.

Article nr	Name	Content	Section
N581206	Novaseal white	310ml	ADHESIVES AND SEALANTS
N599610	Novatwister	1 pc.	TOOLS

