

Q-FIX 120

QIX

SUPERSTRONG AND SUPERFAST CHEMICAL ANCHORING

- The technology if anchoring has to be done, even at freezing temperatures of -5°C!
- Can be used in both dry and damp bore-holes, and even under water.
- Exceptionally chemical and UV resistant.
- Anchors in both solid and hollow bricks, concrete blocks, Ytong, ...
- Extremely long shelf life, 18 months whether opened or unopened.
- · Simple, handy and easy to process.



GENERAL INFORMATION

Q-FIX 120 has been specially developed for heavy load bearing chemical anchors in hollow and solid materials such as stone, concrete, aerated concrete, ... Q-FIX 120 is a waterproof, impermeable attachment.Q-FIX 120 is a vinyl ester

resin that has the best mechanical characteristics and offers better chemical resistance. Q-FIX 120 also has all of the required permits: the European Technical Approval (ETA/CE) option 7 for uncracked concrete and fire class F120.

TECHNICAL INFORMATION AND PACKAGING

Basis: vinyl ester resins. Colour: grey. Odour: weak odour, styrene-free. Temperature resistance:

to +80°C, with peaks to +120°C. Application temperature of the cartridge: +/- 20°C.

Storage: 5 to a maximum of 25°C. Certificates: F120 and ETA.

Adhesion:

very good adhesion on all porous material; less good to poor adhesion on smooth surfaces. Shelf life: 12 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- · CHEMICAL ANCHORING
- to anchor reinforcement rods (concrete construction)
- mounting rails, fences, masts, antennas, sun shields, roll-down shutters, lift casings, heating and cooling systems, ... by using anchored wire
- hooks, bolts, hinges, profiles, ...

Article nr	Name	Content	Section
N315100	Seal & Bond Gun 12:1	1pc.	TOOLS
N610128	Q-Fix 120	280ml	ADHESIVES AND SEALANTS
N610138	Q-Fix 120	380ml	ADHESIVES AND SEALANTS
N610191	O-Fix Mixer Tips	12pcs.	TOOLS



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



