

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### - 1.1 Product identifier

- Trade name: Seal Flex HT red

#### - 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture Silicate sealing

#### - 1.3 Details of the supplier of the safety data sheet

##### - Manufacturer/Supplier:

TECHNIQUA HANDELS GmbH

Reichenhaller Straße 15

D-83451 Piding

Tel: +49 (8651) - 767 62 51

E-Mail: sales@techniqua.de

#### - 1.4 Emergency telephone number: Poison information center

Tel: +49 (0) 6131 - 19240, Langenbeckstraße 1, D- 55131 Mainz

### SECTION 2: Hazards identification

#### - 2.1 Classification of the substance or mixture

##### - Classification according to Regulation (EC) No 1272/2008

Aerosol 3 H229 Pressurised container: May burst if heated.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

#### - 2.2 Label elements

##### - Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

##### - Hazard pictograms



GHS05 GHS07 GHS08

##### - Signal word Danger

##### - Hazard-determining components of labelling:

Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime

2-butanone oxime

3-aminopropyltriethoxysilane

##### - Hazard statements

H229 Pressurised container: May burst if heated.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

##### - Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

**Trade name: Seal Flex HT red**

(Contd. of page 1)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**- Additional information:**

8 % by mass of the contents are flammable

**- 2.3 Other hazards****- Results of PBT and vPvB assessment****- PBT:** Not applicable.**- vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****- 3.2 Mixtures****- Description:** Silicate sealing**- Dangerous components:**

CAS: 2224-33-1 EINECS: 218-747-8	Butan-2-one O,O',O''-(vinylsilyldiyl)trioxime STOT RE 2, H373; Eye Dam. 1, H318; Skin Sens. 1, H317	3-<5%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0	2-butanone oxime Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317	1-<3%
CAS: 919-30-2 EINECS: 213-048-4 Index number: 612-108-00-0 Reg.nr.: 01-2119480479-24-xxxx	3-aminopropyltriethoxysilane Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317	0.3-<1%
In the propellant-mixture:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane Flam. Gas 1, H220; Press. Gas C, H280	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flam. Gas 1, H220; Press. Gas C, H280	

**- Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****- 4.1 Description of first aid measures****- General information:** Immediately remove any clothing soiled by the product.**- After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**- After skin contact:**

After contact with skin, wash immediately with plenty of soap and water.

If skin irritation continues, consult a doctor.

**- After eye contact:**

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**- After swallowing:**

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**- 4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**- 4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

Trade name: Seal Flex HT red

(Contd. of page 2)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**  
Can form explosive gas-air mixtures.  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Do not inhale explosion gases or combustion gases.
- **Additional information**  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Absorb liquid components with liquid-binding material.  
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**  
Fumes can combine with air to form an explosive mixture.  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 10 for information on "stability and reactivity".  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about fire - and explosion protection:**  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Protect from heat and direct sunlight.  
Store under lock and key and with access restricted to technical experts or their assistants only.  
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **Maximum storage temperature:** 30 °C
- **Minimum storage temperature:** 5 °C

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

**Trade name: Seal Flex HT red**

(Contd. of page 3)

**- 7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****- Additional information about design of technical facilities:** No further data; see item 7.**- 8.1 Control parameters****- Ingredients with limit values that require monitoring at the workplace:****96-29-7 2-butanone oxime**

AGW (Germany)	Long-term value: 1 mg/m <sup>3</sup> , 0.3 ppm 8(I);AGS, Y, H, Sh
---------------	----------------------------------------------------------------------

**74-98-6 propane**

AGW (Germany)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm 4(II);DFG
---------------	-----------------------------------------------------------------

**106-97-8 butane**

AGW (Germany)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm 4(II);DFG
---------------	-----------------------------------------------------------------

**- DNELs****919-30-2 3-aminopropyltriethoxysilane**

Oral	Akut, Systemische Effekte	5 mg/kg (all)
	Langzeit, Systemische Effekte	5 mg/kg bw/day (all)
Dermal	Akut, Systemische Effekte	5 mg/kg bw (all) 8.3 mg/kg bw (ber)
	Langzeit, Systemische Effekte	5 mg/kg bw/day (all) 8.3 mg/kg bw/day (ber)
Inhalative	Akut, Systemische Effekte	17.4 mg/m <sup>3</sup> (all) 59 mg/m <sup>3</sup> (ber)
	Langzeit, Systemische Effekte	17 mg/m <sup>3</sup> (all) 59 mg/m <sup>3</sup> (ber)

**- PNECs****919-30-2 3-aminopropyltriethoxysilane**

PNEC Boden	0.04 mg/kg Boden
PNEC Meerwasser	0.033 mg/l
PNEC Süßwasser	0.33 mg/l

**- CAS No. Designation of material % Type Value Unit****- Additional Occupational Exposure Limit Values for possible hazards during processing:****96-29-7 2-butanone oxime**

AGW (Germany)	Long-term value: 1 mg/m <sup>3</sup> , 0.3 ppm 8(I);AGS, Y, H, Sh
---------------	----------------------------------------------------------------------

**67-56-1 methanol**

AGW (Germany)	Long-term value: 270 mg/m <sup>3</sup> , 200 ppm 4(II);DFG, EU, H, Y
IOELV (European Union)	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin

**- Additional information:**

If used according to specifications the propellant (contains propane/butane) is not liberated.  
The lists valid during the making were used as basis.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

**Trade name: Seal Flex HT red**

(Contd. of page 4)

**- 8.2 Exposure controls****- Personal protective equipment:****- General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

**- Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

**- Protection of hands:**

Protective gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**- Material of gloves**

Find below a list of appropriate protective gloves for chemical surrounding:

.

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Naturlatex I , Nr. 0395 oder 0403

Naturlatex II , Nr. 0706 oder 0708

Chloropren Nitril II, Nr. 0717

Chloropren Nitril I, Nr. 0727

Chloropren, Nr. 0720, 0722, 0723, 0725 oder 0726

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Nitril II, Nr. 0740, 0741, 0742 oder 0759

Nitril III, Nr. 0743

Nitril VI, Nr. 0754

Nitril V, Nr. 0764

Viton, Nr. 0890

Butyl II, Nr. 0897

Butyl, Nr. 0898

.

.

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**- Penetration time of glove material**

Permeation time / penetration time: see above (material of gloves)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**- Eye protection: Safety glasses**

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

Trade name: Seal Flex HT red

(Contd. of page 5)

### SECTION 9: Physical and chemical properties

#### - 9.1 Information on basic physical and chemical properties

##### - General Information

##### - Appearance:

Form: Pasty

Colour: Red

- Odour: Characteristic

- Odour threshold: Not determined.

- pH-value: Not determined.

##### - Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

- Flash point: Not applicable.

- Flammability (solid, gas): Not applicable.

##### - Ignition temperature:

Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not self-igniting.

- Explosive properties: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

##### - Explosion limits:

Lower: Not determined.

Upper: Not determined.

- Vapour pressure: Not determined.

- Density at 20 °C: 1.28 g/cm<sup>3</sup>

- Relative density: Not determined.

- Vapour density: Not determined.

- Evaporation rate: Not applicable.

- Solubility in / Miscibility with water:

Hydrolised.

- Partition coefficient: n-octanol/water: Not determined.

##### - Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

- 9.2 Other information: No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity: No further relevant information available.

#### - 10.2 Chemical stability

##### - Thermal decomposition / conditions to be avoided:

Protect from heat and direct sunlight.

No decomposition if used and stored according to specifications.

##### - 10.3 Possibility of hazardous reactions

Danger of bursting.

Toxic fumes may be released if heated above the decomposition point.

- 10.4 Conditions to avoid: No further relevant information available.

- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

**Trade name: Seal Flex HT red**

(Contd. of page 6)

**- 10.6 Hazardous decomposition products:**

No dangerous products of decomposition if used and stored according to specifications.

**SECTION 11: Toxicological information****- 11.1 Information on toxicological effects****- Acute toxicity** Based on available data, the classification criteria are not met.**- LD/LC50 values relevant for classification:****96-29-7 2-butanone oxime**

Oral	LD50	930 mg/kg (rat)
Dermal	LD50	>1000 mg/kg (rab)
Inhalative	LC50/4 h	> 4.83 mg/l (rat)

**106-97-8 butane**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**919-30-2 3-aminopropyltriethoxysilane**

Oral	LD50	1490 - 2690 mg/kg (rat)
Dermal	LD50	4076 mg/kg (rab) (EPA)

**- Primary irritant effect:****- Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.**- Serious eye damage/irritation**

Causes serious eye damage.

Causes serious eye damage.

**- Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**- Additional toxicological information:**

No experimentally found toxicological data are available for this preparation.

**- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Limited evidence of a carcinogenic effect.

**- Germ cell mutagenicity** Based on available data, the classification criteria are not met.**- Carcinogenicity**

Suspected of causing cancer.

**- Reproductive toxicity** Based on available data, the classification criteria are not met.**- STOT-single exposure** Based on available data, the classification criteria are not met.**- STOT-repeated exposure** Based on available data, the classification criteria are not met.**- Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****- 12.1 Toxicity****- Aquatic toxicity:****919-30-2 3-aminopropyltriethoxysilane**

EC50/48 h	331 mg/l (DA) (OECD TG 202)
EC50/72 h	>1000 mg/l (Algae) (OECD TG 201)
LC0/96 h	>934 mg/l (Danio rerio) (OECD TG 203)
NOEC	1.3 mg/l (Algae) (OECD TG 201)

**- 12.2 Persistence and degradability** No further relevant information available.**- 12.3 Bioaccumulative potential** No further relevant information available.**- 12.4 Mobility in soil** No further relevant information available.**- Additional ecological information:****- General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

**Trade name: Seal Flex HT red**

(Contd. of page 7)

Danger to drinking water if even small quantities leak into the ground.  
Do not allow product to reach ground water, water course or undiluted sewage system.  
Water hazard class (German Regulation) is valid for the active agent.

**- 12.5 Results of PBT and vPvB assessment****- PBT:** Not applicable.**- vPvB:** Not applicable.**- 12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****- 13.1 Waste treatment methods****- Recommendation** Disposal must be made according to official regulations.**- Uncleaned packaging:****- Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****- 14.1 UN-Number****- ADR, IMDG, IATA**

UN1950

**- 14.2 UN proper shipping name****- ADR**

1950 AEROSOLS

**- IMDG**

AEROSOLS

**- IATA**

AEROSOLS, flammable

**- 14.3 Transport hazard class(es)****- ADR****- Class**

2 5F Gases.

**- Label**

2.1

**- IMDG, IATA****- Class**

2.1

**- Label**

2.1

**- 14.4 Packing group****- ADR, IMDG, IATA**

Void

**- 14.5 Environmental hazards:**

Not applicable.

**- 14.6 Special precautions for user**

Warning: Gases.

**- Danger code (Kemler):**

-

**- EMS Number:**

F-D,S-U

**- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

(Contd. on page 9)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

**Trade name: Seal Flex HT red**

(Contd. of page 8)

**- Transport/Additional information:****- ADR****- Limited quantities (LQ)**

1L

**- Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

**- Transport category**

2

**- Tunnel restriction code**

D

**- IMDG****- Limited quantities (LQ)**

1L

**- Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

**- UN "Model Regulation":**

UN1950, AEROSOLS, 2.1

**SECTION 15: Regulatory information****- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****- REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48**- National regulations:****- Waterhazard class:**

Water hazard class 2 (Self-assessment): hazardous for water.

Water hazard class (German Regulation) is valid for the active agent.

**- 15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**- Relevant phrases**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

**- Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 3: Aerosols – Category 3

Press. Gas C: Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 10)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 24.03.2017

Version number 3

Revision: 24.03.2017

**Trade name: Seal Flex HT red**

(Contd. of page 9)

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

**- \* Data compared to the previous version altered.**