

CLB

SYNTHETIC, CLEAR PTFE-BASED GREASE

- Unique adherence.
- Resists and prevents corrosion.
- Excellent penetration.
- Maintains viscosity at high and low temperatures.
- Resists pressure cleaning.
- Extends lubrication intervals.
- Reduces chain tension and wear.
- Has a clean, transparent overspray.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

CLEAR LUBE

GENERAL INFORMATION

CLEAR LUBE is a specially formulated lubricant, based on acrylic copolymers and neutral, synthetic oils, mixed with aliphatic and some aromatic oil derivatives, in order to increase the running-in effect. CLEAR-LUBE contains PTFE in order to increase the life span and to reduce the sliding resistance. CLEAR-LUBE has been formulated to offer a high lubrication capacity at high pressure and in difficult conditions. CLEAR-LUBE both

protects against corrosion because of the formation of a thin polymer film, and penetrates deeply into the objects that have to be lubricated. CLEAR-LUBE can be used in a wide temperature range, without any change of viscosity. Due to its high adhesive capacity, CLEAR-LUBE is resistant to high-pressure cleaning. CLEAR-LUBE reduces chain friction and wear and extends chain life up to 10 fold.

TECHNICAL INFORMATION AND PACKAGING

Specific weight: 0.885.
Solid substances: approx. 30%.
Temperature range: -25°C until +300°C.
Viscosity : on application: 48sec. - B6 FLOW cup; after evaporation of solvent: 6 min. 6 sec. - B6 FLOW cup.
Basis: acrylic - copolymers is neutral oil.
Solvent: aliphatic hydrocarbons with some aromatics.

Additives: PTFE.

Shelf life: 12 months, keep dry, cool and frost-proof.
Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- has been formulated for indoor and outdoor heavy duty lubrication
- extremely effective on intermittent and inaccessible lubrication points
- is suitable for most types of industry, typically on chains, conveyors, open gears, wire-rope, cables, joints, linkages, lead screws, hinges, locking mechanisms
- effective on rubber "O"-ring chains
- is particularly useful where equipment has to withstand severe conditions such as outdoor exposure or contact with acids, alkalis, hot & cold water and steam

Article nr	Name	Content	Section
N214001	Clear Lube	400ml	LUBRICANTS

