

MTS

UNIQUE RUST-CONVERTING AND RUST-PREVENTING TECHNOLOGY

- METALSOL converts rust into a remaining, stabilised and impenetrable layer.
- METALSOL neutralises rust through a visible reaction.
- METALSOL is economical and cost-cutting.
- METALSOL is an ideal undercoat or final layer in one product and can be applied easily with a brush or with a spray gun.
- METALSOL can be used curatively and preventively.
- METALSOL can be painted or filled after drying (+/- 50 min).
- METALSOL is safe to use.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

METALSOL

GENERAL INFORMATION

Rust is a complex molecular combination of unstable iron oxides and hydroxides with a strong hygroscopic character. When removing rust superficially, small rust particles will often remain in the pores of the surface, which will spontaneously reactivate the corrosion process after a while. In order to solve this ancient problem in a professional way, we have developed METALSOL. It is a milky coloured synthetic emulsion that will convert the iron oxides into a tough, black layer after contact with steel and

under the influence of air humidity. The metal organic layer obtained after curing will protect the surface against new rust formation.

METALSOL doesn't only function as a rust converter, but at the same time as ideal undercoat for the application of the most common paint systems. This will protect the surface, provide it with an undercoat, make it free from rust in one action, and will undoubtedly save hourly wages and product costs. METALSOL is water- and solventproof after cure.

TECHNICAL INFORMATION AND PACKAGING

Composition/Appearance: milky synthetic emulsion based on acrylic copolymer resins and anti-oxidants, which will cure to a half-shiny black finish layer after reacting with rust.

Viscosity: Ford Cup N°4: 45 sec. (mPa.s)

Content of solids: 52%

pH: 1.5

Specific gravity: 1.25 kg/dm³

Flashpoint: closed cup > 30°C

Inflammability: dry film is flame-retarding

Processing temperature: min. 5°C - max. 40°C

Drying times: summer: 15 min.; winter: 45 min.

High humidity and low temperatures decelerate drying. Use an IR-lamp or hot air circulation to accelerate drying.

Salt spray test: ASTM B117 resistance > 5000 h.

Temperature resistance: -60°C to +150°C.

Shelf life: 12 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- preventively and curatively treats rust in all industrial applications: car body shops, restoration works, maintenance and repairs, ...

Article nr	Name	Content	Section
N119025	Metalsol	5l	SURFACE PROTECTION AND TREATMENT
N119029	Metalsol	1l	SURFACE PROTECTION AND TREATMENT
Y875000	Trigger Basic	12pcs.	TOOLS
Y875001	Trigger Solvent Resistant	12pcs.	TOOLS
Y875002	Standard Bottle 1l	1 pc.	TOOLS

