

NLO

UNIQUE TECHNOLOGY FOR SAFELY TRACING OIL AND FUEL LEAKS

- Time saving: traces leaks quickly and efficiently.
- Is compatible with all oil types.
- Very easy and safe to use.
- Can stay permanently in the fluid for future inspections.
- Appropriate for all motors, differential, gearboxes, steering boxes and hydraulic systems.
- Can be used safely in all fuel systems with petrol as well as diesel.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

NOVALEAK OIL

GENERAL INFORMATION

NOVALEAK OIL prevents the long search for possible leaks.

NOVALEAK OIL quickly traces seepage through of oils and fuels in installations.

NOVALEAK OIL can be left in the system permanently and therefore simplifies future inspections.

NOVALEAK OIL will give a fluorescent effect after mixing with oil or

fuel.

With the help of NOVALEAK LAMP the fluorescent contrast will become clearly visible.

The NOVALEAK LAMP is delivered together with UV safety goggles.

They protect the eyes against UV-light and make the contrast liquid even more visible.

NOVALEAK OIL can also be used preventively.

TECHNICAL INFORMATION AND PACKAGING

Appearance: liquid.

Composition: 80 to 90% oil based.

Odour: light oil odour.

Solubility: mixable with all oils and fuels; insoluble with water.

Colour: dark red.

Mixture: NOVALEAK OIL mixed with oil or fuel gives a fluorescent effect.

Consumption: 30 ml NOVALEAK OIL deals with:

- 5 litres of motor oil

- 8 litres of transmission or hydraulic oil

- 15 litres of fuel (petrol or diesel)

Cleaning: remainders can be cleaned with NOVATIO SAFETY CLEAN or KLEENSpray-S.


Shelf life: 12 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- ideal to trace leaks at the engines, the gearbox, the differential, hydraulic steering houses, suspension, hydraulic operations on machines, differential cabinets, fuel leaks with cars, motorcycles, trucks, farming machinery, burners, ...

Article nr	Name	Content	Section
N750121	Novaleak Oil	30ml	ADDITIVES



ADDITIVES

WWW.TECH-MASTERS.EU

