

## NOG-NOB

### UNIQUE TECHNOLOGY FOR THE FIGHT AGAINST ALL OIL LEAKAGES

- Stops and prevents dehydration or hardening of all synthetic sealing rings and gaskets.
- Makes rubbers soft and flexible and reusable.
- Can be used for preventive and curative maintenance.
- Is compatible with all oil types.
- No chlorides or solvents.
- Does not contain oil thickeners.
- Extremely well suited for diesel and petrol engines, hydraulic systems, hydro-pneumatic spring systems, gearboxes, ...
- A perfect result, even with thick differential oil.
- Prevents expensive repairs or replacements.
- 1 treatment is adequate.
- Safe to use.



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

## NOVASTOP OIL

### GENERAL INFORMATION

NOVASTOP OIL prevents expensive disassembly and assembly costs for replacement of leaking seals.

NOVASTOP OIL conditions seals, protects them against dehydration, hardening, shrinking and crystallisation.

NOVASTOP OIL impregnates the leaking seals, makes them elastic again, lets them swell in a controlled way and rules out oil leakages for a long time.

NOVASTOP OIL IS AVAILABLE IN TWO VERSIONS:

NOVASTOP OIL GREEN: Engine applications. For seals and the conditioning of rubbers, carters, valve covers, coupling pieces, detachable parts,

camshaft, crankshaft, ... Very suitable for turbo, petrol and LPG-engines.

NOVASTOP OIL BLUE: Transmission applications. For the sealing and conditioning of sealing rings and gaskets of differentials, automatic and hand-change gearboxes, hydraulic systems on forklift trucks and cranes, hydropneumatic spring systems. Prevents whistling and squeaking of power steering, ... Also suitable for ATF, hydraulic and mineral oils, ...

NOVASTOP OIL as a preventive treatment is recommended for engines and installations as from 3 years old.

### TECHNICAL INFORMATION AND PACKAGING

Composition: liquid oily mixture of selected rubber softeners.

Odour: slight oily smell.

Density: ca 1.15 +/-0.1 kg/dm<sup>3</sup>.

Solubility: mixable with all oils; soluble in solvents and insoluble in water.

Flashpoint: 235°C.

Consumption: NOG: 30 ml/l oil; NOB: 35 ml/l oil.

Shelf life: 12 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

### APPLICATION AND USE

- effective on all rubber seals and most cork seals in diesel and petrol engines, hydraulic systems, hydro pneumatic spring systems, gearboxes, etc.
- combating oil leaks in closed oils systems

Article nr	Name	Content	Section
N742103	Novastop Oil green	250ml	ADDITIVES
N742203	Novastop Oil blue	250ml	ADDITIVES



ADDITIVES

WWW.TECH-MASTERS.EU

