

# PRO

### THE PROFESSIONAL **PROTECTIVE TEXTILE TAPE**

- · A wear-resistant PET-coat finished with textile.
- · Easy to apply.
- Permits the protection of a closed circuit. Perfect protection, even on difficult
- materials such as e.g. silicone cables, ... Prevents cracking, squeaking, vibrations and wear.
- Esthetical repair for an original look.
- Resists ageing.
- Temperature resistance from -30°C to +110°C.
- Ideal for repair or tap of wire bundles, cable trees, pipes, ...



# **GENERAL INFORMATION**

NOVA PRO TAPE is a tape that is specially developed to protect cable trees, cable hoses, pipes and tubes manually. The tape has a good temperature resistance and

is sound-insulating. NOVA PRO TAPE resists ageing and rotting. Thanks to the woolly textile and very thin structure of NOVA PRO TAPE overlappings are almost invisible.

**NOVA PRO TAPE** 

#### NOVA PRO TAPE has a fast immediate adhesiveness on most materials. Based on: PET. Top coat: woolly textile. Adhesive: rubber adhesive. Colour: black. Tensile strength: 40 N/cm. Elongation after fracture: 10-25%. Total thickness: 0.3 mm.

# · gives your repair an original look

• for the installation of LPG

- protection of cables in dashboard or switch boxes against vibrations
- protection of cables, tubes, wires, pipes

**APPLICATION AND USE** 

- bundling of cables
- wrapping of repaired wires or bundles •

Name



Shrink: 0.3 mm

Nova Pro Tape 19mm x 10m

Content



# NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.





WWW.TECH-MASTERS.EU

**TECHNICAL INFORMATION AND PACKAGING** 

tuning

1pc.

Solvents: free.

Adhesive power: > 1.5 N/cm.

Temperature resistance: from -30°C to +110°C. Attention: after 24 hours it is 100% optimum. First test foundations based on PE, PP, silicones and bitumen for adhesion (see each tape). Shelf life: 24 months, keep dry, cool and frost-proof. Safety measures: consult the Safety Data Sheet.

Section

TAPES