

# **LTP-S19**

### THE LIGHT WEIGHT AND HAND HELD TORCH SYSTEM

- Automatic piezo ignition
- Trigger on/off function no waste of LP gas
- Operates in all positions
- Wide range of quick changeable burners
- For disposable cartridges
- Ergonomic light weight composite handle or sturdy heavy duty metal handle
- Provides a flame temperature of 1925° C.



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

# **LOTPISTOLE SOFT 1925**

## **GENERAL INFORMATION**

The blowtorch for Do-It-Yourself applications I ike soft soldering, loosening bolts, paintstripping,

lighting the barbeque!

For use with disposable cartridges 2203 and 2204.

• 8708: Hot-air burner for shrinking and paint

stripping. Powerful and wind stable hot-air

jobs. Powerful and wind stable soft flame.

Gas consumption, at 2 bar: 130g/h

Gas consumption, at 2 bar: 230g/h

#### **TECHNICAL INFORMATION**

TECHNICAL INFORMATION Working pressure: 1 bar

For ultragas catridge (not included): 2204 Can be used with burner 8702, 8704, 8706, 8708, 8710.

stream.

NO BURNER INCLUDED!

Burner diameter: 38mm

Effect, at 2 bar: 1,7kW

Burner diameter: 24 mm

Effect, at 2 bar: 3,5 kW

### **TECHNICAL INFORMATION BURNER**

- 8702 : Pin-point burner for small soft soldering jobs. Gives a precise and stable flame. Burner diameter: 15mm Gas consumption, at 2 bar: 40g/h Effect, at 2 bar: 0,5kW Soft soldering at 2 bar: 10mm
- 8704: Standard burner for soft soldering and other small heating jobs. For soft soldering and other small heating jobs. Burner diameter: 16 mm Gas consumption, at 2 bar: 90g/h Effect, at 2 bar: 1,2kW
- 8706: Cyclone burner for brazing and soft soldering. Intensive and effective short flame that reaches around the pipe.

Burner diameter: 14 mm Gas consumption, at 2 bar: 170g/h Effect, at 2 bar: 2,2kW Soft soldering: 40 mm

Brazing at 2 bar: 18mm

Soft soldering at 2 bar: 18mm

Soft soldering at 2 bar: 22 mm 8843: Copper bit: Made f copper with one pointed and one flat end. For use with burner 8702.

8710:Soft flame burner for shrinking and heating

Article nr	Name	Content	Section
Y902203	Powergas 1925°C	300ml	TOOLS
Y902204	Powergas 1925°C	600ml	TOOLS
Y902235	Lotpistole Soft 1925	1 pc.	TOOLS
Y902282	Lotpistole Handy	1 pc.	TOOLS
Y908702	Pin-Point Burner	1 pc.	TOOLS
Y908704	Standard Burner	1 pc.	TOOLS
Y908708	Hot-Air Burner	1 pc.	TOOLS
Y908710	Soft Flame Burner	1 pc.	TOOLS
Y908843	Copper Bit	1 pc.	TOOLS
Y993257	Case (empty)	1 pc.	TOOLS











T908702







T908843



