

Page 1/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2016 Version number 11 Revision: 09.06.2016

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Hardener for Putty HD / Putty HD flex
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

TECHNIQUA HANDELS GmbH

Reichenhaller Straße 15

D-83451 Piding

Tel: +49 (8651) - 767 62 51 E-Mail: sales@techniqua.de

· 1.4 Emergency telephone number:

Poison information center

Tel: +49 (0) 6131 - 19240, Langenbeckstraße 1, D- 55131 Mainz

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Org. Perox. E H242 Heating may cause a fire.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.



Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 09.06.2016 Printing date 15.06.2016

Version number 11



(Contd. of page 1)

Trade name: Hardener for Putty HD / Putty HD flex

· Hazard pictograms







GHS02

GHS07

#### · Signal word Warning

#### · Hazard-determining components of labelling:

dibenzoyl peroxide

#### · Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Store at temperatures not exceeding  $30^{\circ}\text{C}$ . Keep cool. P411+P235

P501 Dispose of contents / container in accordance with regional regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 94-36-0	dibenzoyl peroxide	25-<50%
EINECS: 202-327-6	🔗 🚳 Org. Perox. B, H241	
Index number: 617-008-00-0	V	
Reg.nr.: 01-2119511472-50	Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 5444-75-7	2-etilesil benzoato	20-<25%
EINECS: 226-641-8	Aquatic Chronic 4, H413	

#### · Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31 Revision: 09.06.2016

Printing date 15.06.2016 Version number 11

Trade name: Hardener for Putty HD / Putty HD flex

(Contd. of page 2)

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Larger fires with water spray or foam. Cool containers with water *Use fire extinguishing methods suitable to surrounding conditions.* 

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow to enter sewers/surface or ground water.

Do not allow product to reach sewage system or any water course.

- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special measures required.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 5.2
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

94-36-0 dibenzoyl peroxide

WEL Long-term value: 5 mg/m<sup>3</sup>

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 09.06.2016 Printing date 15.06.2016

Version number 11



(Contd. of page 3)

Trade name: Hardener for Putty HD / Putty HD flex

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Otherwise, filter class A / P2 or self contained.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:



Protective gloves

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

· Eye protection: Safety glasses

CHOMIC	AT O TO		<b>,</b> , ,	
	V 9: P	nvsical and	l chemical	properties

•			
· 9.1 Information on basic physical and chemical properties			
	· General Information		
· Appearance:	_		
Form:	Pasty		
Colour:	Pink		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
· pH-value:	Not applicable.		
· Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	197 °C		
· Flash point:	111 °C		
· Flammability (solid, gaseous):	May cause fire.		
· Ignition temperature:	410 °C		
· Decomposition temperature:	Not determined.		
· Self-igniting:	Product is not selfigniting.		
· Danger of explosion:	Product does not present an explosion hazard.		
· Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
· Vapour pressure at 20 °C:	1 hPa		
· Density at 20 °C:	$1.15 \ g/cm^3$		
· Relative density	Not determined.		
· Vapour density	Not applicable.		
· Evaporation rate	Not applicable.		

(Contd. on page 5)

# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 09.06.2016 Printing date 15.06.2016

Version number 11



Trade name: Hardener for Putty HD / Putty HD flex

		(Contd. of page
· Solubility in / Miscibility with		
water:	Insoluble.	
· Partition coefficient (n-octano	l/water): Not determined.	
· Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
· Solvent content:		
VOC-(EU)	%	
· VOC-EU%	0.00 %	
· Solids content:	73.0 %	
· 9.2 Other information	No further relevant information available.	

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 6)

# Safety data sheet according to 1907/2006/EC, Article 31

 Revision: 09.06.2016
 according to 19

 Printing date 15.06.2016
 Versi

Version number 11



Trade name: Hardener for Putty HD / Putty HD flex

(Contd. of page 5)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	· European waste catalogue	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
15 01 02	plastic packaging	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN3108
· 14.2 UN proper shipping name	
$\cdot ADR$	UN3108 ORGANIC PEROXIDE TYPE E, SOLII
· IMDG	ENVIRONMENTALLY HAZARDOUS ORGANIC PEROXIDE TYPE E, SOLID, MARIN POLLUTANT
·IATA	Organic peroxide type E, solid
· 14.3 Transport hazard class(es)	
· ADR, IMDG	
· Class · Label	5.2 Organic peroxides. 5.2
· IATA	
· Class	5.2 Organic peroxides.
· Label	5.2
· 14.4 Packing group	
· IMDG	III
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
2 0 7	, v ,

(Contd. on page 7)

# Safety data sheet according to 1907/2006/EC, Article 31

 techni

Trade name: Hardener for Putty HD / Putty HD flex

	(Contd. of page
EMS Number:	F-J,S-R
Stowage Category	D
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SG35 Stow "separated from" acids.
	SG36 Stow "separated from" alkalis.
14.7 Transport in bulk according to Anno	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	500 g
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	5 kg
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 1000 g
UN ''Model Regulation'':	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID, 5.2
	ENVIRONMENTALLY HAZARDOUS

# **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H241 Heating may cause a fire or explosion.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H413 May cause long lasting harmful effects to aquatic life.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. B: Organic Peroxides, Type B

Org. Perox. E: Organic Peroxides, Types E, F

(Contd. on page 8)

Page 8/8

# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 09.06.2016 Printing date 15.06.2016

Version number 11



(Contd. of page 7)

Trade name: Hardener for Putty HD / Putty HD flex

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4