Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

·Trade name: ZINC GUARD

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Spray varnish
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

TECHNIQUA HANDELS GmbH

Reichenhaller Straße 15

D-83451 Piding

Tel: +49 (8651) - 767 62 51 E-Mail: sales@techniqua.de

·1.4 Emergency telephone number: Poison information center

Tel: +49 (0) 6131 - 19240, Langenbeckstraße 1, D- 55131 Mainz

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

CHSUG

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 1)

#### · Signal word Danger

### · Hazard-determining components of labelling:

Acetone

Hydrocarbons, C9, aromatics

butanol

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment. P280 Wear protective gloves / eye protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- $\cdot \ Results \ of \ PBT \ and \ vPvB \ assessment$
- PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: Active substance with propellant

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
		(Contd. on page 3)

(Contd. on page 3)

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

		(Contd. of page 2)
EC number: 918-668-5	Hydrocarbons,C9,aromatics	2.5-<10%
Reg.nr.: 01-2119455851-35	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	
CAS: 7440-66-6	zinc powder -zinc dust (stabilized)	1-<2.5%
EINECS: 231-175-3 Reg.nr.: 01-2119467174-37	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 71-36-3	butanol	1-<2.5%
EINECS: 200-751-6	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302;	
Reg.nr.: 01-2119484630-38	Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
FG 1 010 401 0		0.1 -10/
EC number: 918-481-9	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene	0.1-<1%
Reg.nr.: 01-2119457273-39	<0.1%	-
	Asp. Tox. 1, H304	
CAS: 7779-90-0	trizinc bis(orthophosphate)	≥0.25-<1%
EINECS: 231-944-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119463881-32		
CAS: 1314-13-2	zinc oxide	≥0.1-<0.25%
EINECS: 215-222-5	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119463881-32		

· Additional information:

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 3)

#### • 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

### · Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

### · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

### · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

## $\cdot$ Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

### · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

· Additional information about design of technical facilities: No further data; see item 7.

### $\cdot$ 8.1 Control parameters

<ul> <li>Ingredients with limit value</li> </ul>	alues that require	e monitoring at the	workplace:
--	--------------------	---------------------	------------

#### **67-64-1** Acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

### 106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 5)

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

74-98-6 p	ronane		(Contd. of page
_	ort-term value: 3600 m	ισ/m³ ′	2000 ppm
	ng-term value: 1800 m		
71-36-3 b		<i>U</i> /	11
	ort-term value: 154 mg	/m³, 50	) man
Sk		,, ,	· FF
Hydrocar	bons,C10-C13,n-alk	anes,cy	yclic,<2% aromates, Benzene <0.1%
OEL Sho	ort-term value: 1200 m	ig/m³, 1	184 ppm
DNELs			
67-64-1 A	cetone		
Oral		stemic	62 mg/kg bw/day (Consumer)
Dermal	1		62 mg/kg bw/day (Consumer)
20111111	21 (22 Zong term sj		186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local		2,420 mg/m3 (Worker)
111111111111111111111111111111111111111		stemic	200 mg/m3 (Consumer)
	Zitzz zong term sy		1,210 mg/m3 (Worker)
Hydrocar	bons,C9,aromatics		1,210 mg/m3 (Worker)
Oral		stemic	11 mg/kg bw/day (Consumer)
Dermal	1		11 mg/kg bw/day (Consumer)
Dermai	DIVEL Long term-sy	sterine	25 mg/kg bw/day (Worker)
Inhalativa	DNEL Long term sy	stamic	
IIIIaiaiive	Inhalative DNEL Long term-system		
7440 66 6	100 mg/m3 (Worker)		
Oral	6 zinc powder -zinc dust (stabilized)  DNEL Long term-systemic   50 mg/kg bw/day (Worker)		
Dermal	• •		5,000 mg/kg bw/day (Consumer)
Dermai	DIVEL Long term-sy	sterric	5,000 mg/kg bw/day (Consumer)
Inholotiva	DNEL Long term sy	stamia	2.5 mg/m3 (Consumer)
IIIIaiaiive	DIVEL Long term-sy	Sterric	5 mg/m3 (Worker)
71-36-3 b	utanal		3 hig/hi3 (worker)
Oral		stamia	3.125 mg/kg bw/day (Worker)
	DNEL Long term-lo		310 mg/m3 (Consumer)
IIIIaiaiive	DNEL Long term-10	cai	55 mg/m3 (Worker)
			55 hig/hi5 (worker)
PNECs			
67-64-1 A		1000	XX 1.0 0
			Undefind)
		`	Undefind)
			Undefind)
		,	Undefind)
	zinc powder -zinc d		
PNEC Fre		,	Undefind)
PNEC Ma			Indefind)
	shwater sediment	`	Jndefind)
PNEC Soi		`	Undefind)
PNEC Sewage Treatment Plant 52 (Une		52 (U	
	rine water sediment		Undefind)

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

**Trade name: ZINC GUARD** 

(Contd. of page 5)

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· Personal protective equipment:

### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

#### Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5$  mm

### · Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye protection:

Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

GB

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 6)

9.1 Information on basic physical and c	hemical properties
General Information	
Appearance: Form:	Aerosol
colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Not applicable, as aerosol.
Flash point:	-97 °C
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	13 Vol %
Vapour pressure at 20 °C:	4 hPa
Density at 20 °C:	0.71 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
<b>Solvent content:</b>	
Organic solvents:	90.3 %

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

CD

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 7)

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:				
67-64-1 A	67-64-1 Acetone				
Oral	LD50	5,800 mg/kg (rat)			
Dermal	LD50	7,800 mg/kg (rbt)			
Inhalative	LC50/4h	>20 mg/l (rat)			
Hydrocar	bons,C9,a	romatics			
Oral	LD50	3,295 mg/kg (rat)			
Dermal	LD50	>3,160 mg/kg (rat)			
7440-66-6 zinc powder -zinc dust (stabilized)		ler -zinc dust (stabilized)			
Oral	LD50	>2,000 mg/kg (rat)			
Inhalative	LC50/4h	>5.4 mg/l (rat)			
71-36-3 bu	ıtanol				
Oral	LD50	2,292 mg/kg (rat)			
Dermal	LD50	3,430 mg/kg (rbt)			
Inhalative	LC50/4 h	>17.76 mg/l (rat)			
7779-90-0	trizinc bis	s(orthophosphate)			
Oral	LD50	5,000 mg/kg (rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- $\cdot \textbf{Respiratory or skin sensitisation} \ \text{Based on available data, the classification criteria are not met.} \\$
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· 12.1 Toxicity		
· Aquatic toxicity:		
67-64-1 Aceton	e	
EC50	8,800 mg/l (Daphnia magna)	
	8,300 mg/l (Fish)	
Hydrocarbons,C9,aromatics		
NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)	
EL50(48h)	3.2 mg/l (Daphnia magna)	
LL50 (96h)	9.2 mg/l (Oncorhynchus mykiss (96h))	
7440-66-6 zinc powder -zinc dust (stabilized)		
EC50	354 ug/l (Daphnia Magna 48h)	
	(C (1 0)	

(Contd. on page 9)

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

		(Contd. of page 8)
NOEC/21d	178 ug/l (Crustaceeen-Palaemon elegans)	
NOEC (72h)	9 mg/l (Ceratophyllum demersum)	
	0.017 mg/l (Pseudokirchneriella subcapitata)	
NOEC/72h	72.9 ug/l (Pseudokirchneriella subcapitata)	
NOEC/4w	8.3 ug/l (Cyprinus carpio)	
EC10/21d	59.2 ug/l (Daphnia magna)	
EC10/72h	27.3 ug/l (algae)	
EC50 (72h)	0.17 mg/l (Selenastrum capricornatum (72 h))	
LC50/96h	0.41 mg/l (Oncorhynchus mykiss)	
EC50/48h	1 mg/l (Daphnia magna)	
EC50/96h	0.527 mg/l (algae)	
LC50	238-269 ug/l (Pimephales promelas (96 h))	
71-36-3 butanol		
NOEC (21 days)	4.1 mg/l (Daphnia magna)	
LC50/96h	1,376 mg/l (Pimephales promelas)	
EC50/48h	1,328 mg/l (Daphnia magna)	
EC50	225 mg/l (Selenastrum capricornatum (72 h))	
7779-90-0 trizinc bis(orthophosphate)		
LC50/96h	0.14 mg/l (Oncorhynchus mykiss (96h))	
EC50/48h	2.34 mg/l (Daphnia magna)	
ErC(50) (72h)	0.14 mg/l (Desmodesmus subspicatus)	
10 0 D	and the collaboration binds and date	

- 12.2 Persistence and degradability Easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

GI

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 9)

14.1 JIN N	
14.1 UN-Number ADR, ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR, ADN	UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
IMDG	AEROSOLS (Hydrocarbons, C9, aromatics, zinc powder zinc dust (stabilized)), MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
ADN	
ADN/R Class:	2 5F
Class Label	2.1 2.1
IATA	
Class Label	2.1 2.1
14.4 Packing group	2.1
ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances: zinc powder -zinc dust (stabilized) Yes
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from"

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

	(Contd. of page
	class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Anno	ex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
- · · · · · · · · · · · · · · · · · · ·	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY
	HAZARDOUS

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations:

Class	Share in %
NK	75-<100

- · VOC-CH 90.31 %
- · VOC-EU 642.1 g/l
- · Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

(Contd. on page 12)

Printing date: 23.02.2018 Version: 31 Revision: 23.02.2018

Trade name: ZINC GUARD

(Contd. of page 11)

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered. \*