

STRIPFIX

SFX

TRANSPARENT GLUE ON **CARRIER FOIL, FOR INSTANT BONDING**

- · Requires no drying time.
- Safe to use, contains no solvents.
- Holds up to 8 kg/cm².
- Cut a suitable piece, press together and it's ready!
- · Good resistance to water, diluted acids, alkalines, mineral oils, ...
- Does not dry out or harden.
- Can be used as a sealant.



GENERAL INFORMATION

STRIPFIX is a synthetic, pressure-sensitive rubber/resin adhesive and sealant. It has been designed to provide a highly aggressive bond between a wide variety of materials and substrates.

STRIPFIX can be used immediately on clean, dry and non-porous surfaces.

STRIPFIX is excellent for bonding "difficult" materials such as glass, metal, wood, rubber and plastics including polyethylene.

TECHNICAL INFORMATION AND PACKAGING

Elongation: 1000%. Initial adhesive strength: 52 N/cm². Tensile strength: 60 N/cm² after 10 min.; 80 N/cm2 after 24 hours. Application weight: 405 g/m2. Temperature resistance: -10°C to +50°C. Application temperature: > +10°C. Water absorption: 0%.

Pressure needed to achieve 20% compression: 1,6 kg/cm².

U.V. resistance: bad - exposure to UV light should be avoided.

Tolerance: thickness and width < 10%. Shelf life: 12 months, keep dry, cool and frost-proof. Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- BUILDING
 - mounting of asbestos connections for protective plates of drain pipes, insulating material in polypropylene, filter membranes for road construction bonding of light insulating plates, connection in synthetic material, ..
- FURNITURE INDUSTRY mounting of laminated decorative frames fixing of corners at furniture
- · CAR INDUSTRY fixing of insulating material, name-plates and signs,
- CONSTRUCTION bonding of side and roof panels on carrier of caravans

Article nr Content Name Section



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



