

according to Regulation (EC) No 1907/2006

#### Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Benzine HP 300ml

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Additive

# 1.3. Details of the supplier of the safety data sheet

Company name: TECHNIQUA Handels GmbH E-Mail:sales@techniqua.de

Street: Reichenhaller Str. 15
Place: D-83441 Piding
Telephone: +49 (0) 8651 767 6251

1.4. Emergency telephone Poison information center

number: Tel: +49 (0) 6131 - 19240, Langenbeckstraße 1, D- 55131 Mainz

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3
Specific target organ toxicity - repeated exposure: STOT RE 1

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects.

# 2.2. Label elements

### Regulation (EC) No. 1272/2008

# Hazard components for labelling

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)

2-Propanol

Signal word: Danger

Pictograms:









# **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

#### Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 2 of 13

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapours.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.
P280 Wear eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

## 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification	•	•		
64742-82-1	Hydrocarbons, C9-C12, n-alkanes,	isoalkanes, cyclics, aromatics (2-2	5 %)	50 - <= 100 %	
	919-446-0		01-2119458049-33		
	Flam. Liq. 3, STOT SE 3, STOT RE H411 EUH066	1, Asp. Tox. 1, Aquatic Chronic 2;	H226 H336 H372 H304		
67-63-0	2-Propanol			10 - < 20 %	
	200-661-7	603-117-00-0	01-2119457558-25		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE	3; H225 H319 H336			
337367-30-3	1-Propene, 2-methyl-, homopolyme	ion products with ammonia	1 - < 3 %		
	Skin Irrit. 2, Aquatic Chronic 3; H31				
173140-85-7	Oxirane, ethyl-, homopolymer, mon		1 - < 3 %		
	Skin Irrit. 2; H315				
110-25-8	N-methyl-N-[C18-(unsaturated)alka		0.1 - < 1 %		
	701-177-3	7.137	01-2119488991-20		
	Acute Tox. 4, Skin Irrit. 2, Eye Dam	. 1, Aquatic Acute 1; H332 H315 H3	318 H400		
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-		0.1 - < 1 %		
	202-414-9		01-2119777867-13		
	Acute Tox. 4, Skin Corr. 1C, STOT H302 H314 H373 H400 H410	10), Aquatic Chronic 1;			

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

#### Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 3 of 13

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

#### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

#### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

## Unsuitable extinguishing media

High power water jet.

## 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.



according to Regulation (EC) No 1907/2006

#### Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 4 of 13

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

# Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

## Further information on handling

Avoid contact with skin and eyes.

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

# Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

# Further information on storage conditions

Store in a cool dry place. Observe legal regulations and provisions.

# 7.3. Specific end use(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL



according to Regulation (EC) No 1907/2006

Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 5 of 13

## **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine				
Worker DNEL,	long-term	inhalation	systemic	0,8 mg/m³	
Worker DNEL,	long-term	dermal	systemic	20 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	0,4 mg/m³	
Consumer DNEL, long-term dermal systemic 10 mg/kg bw/d				10 mg/kg bw/day	
Consumer DN	EL, long-term	oral	systemic	10 mg/kg bw/day	
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol				
Worker DNEL,	long-term	inhalation	systemic	0,46 mg/m³	
Worker DNEL,	acute	inhalation	systemic	14 mg/m³	
Worker DNEL, long-term		dermal	systemic	0,06 mg/kg bw/day	
Worker DNEL,	acute	dermal	systemic	2 mg/kg bw/day	

#### **PNEC values**

CAS No	Substance				
Environmental compartment Value					
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine				
Freshwater		0,00043 mg/l			
Freshwater (int	ermittent releases)	0,0043 mg/l			
Marine water		0,000043 mg/l			
Freshwater sec	liment	0,007 mg/kg			
Marine sediment 0,001 mg/kg					
Micro-organism	Micro-organisms in sewage treatment plants (STP) 1 mg/l				
Soil 1,71 mg/kg					
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol				
Freshwater		0 mg/l			
Freshwater (int	ermittent releases)	0 mg/l			
Marine water		0 mg/l			
Freshwater sediment 0,376 mg/kg					
Marine sediment 0,038 mg/kg					
Micro-organism	s in sewage treatment plants (STP)	0,27 mg/l			
Soil		0,075 mg/kg			

# Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

blood (B) Urine (U)

# 8.2. Exposure controls

## Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.



according to Regulation (EC) No 1907/2006

# Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 6 of 13

#### Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### Eye/face protection

Suitable eve protection: Tightly sealed safety glasses.

**DIN EN 166** 

#### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

**FN ISO 374** 

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: A

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

#### **Environmental exposure controls**

Observe legal regulations and provisions.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: yellow
Odour: amine-like

Test method

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

Sublimation point:

No information available.

Softening point:

No information available.

No information available.

Flash point: <13 °C ISO 3679

**Flammability** 

Solid: not applicable
Gas: not applicable
Lower explosion limits: 0,6 vol. %
Upper explosion limits: 12 vol. %

Ignition temperature: No information available.

**Auto-ignition temperature** 

Solid: not applicable
Gas: not applicable



according to Regulation (EC) No 1907/2006

Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 7 of 13

Decomposition temperature: not determined

**Oxidizing properties** 

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,756 g/cm³ DIN 51757

Water solubility:

The study does not need to be conducted

because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: No information available. DIN 53019-1

Viscosity / kinematic: < 7 mm²/s DIN EN ISO 3104

(at 40 °C)

Flow time: No information available. DIN EN ISO 2431

(at 20 °C)

Vapour density:not determinedEvaporation rate:not determinedSolvent separation test:No information available.Solvent content:No information available.

9.2. Other information

Solid content: not determined

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Flammable, Ignition hazard.

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

#### 10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharges.

#### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

# 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **Further information**

Do not mix with other chemicals.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Toxicocinetics, metabolism and distribution

No information available.



according to Regulation (EC) No 1907/2006

#### Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 8 of 13

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
64742-82-1	Hydrocarbons, C9-C12,	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)							
	oral	LD50 mg/kg	> 15000	Rat	OECD 401				
	dermal	LD50 mg/kg	3400	Rabbit	OECD 402				
	inhalation (4 h) vapour	LC50 mg/l	13100	Rat	OECD 403				
67-63-0									
	oral	LD50 mg/kg	5280	Rat					
	dermal	LD50 mg/kg	> 2000	Rabbit					
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat					
110-25-8	N-methyl-N-[C18-(unsatu	urated)alkano	yl]glycine						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1981)	OECD Guideline 401			
	inhalation vapour	ATE	11 mg/l						
	inhalation (4 h) aerosol	LC50	1,37 mg/l	Rat					
95-38-5	2-(2-heptadec-8-enyl-2-i	midazolin-1-y	l)ethanol						
	oral	LD50 mg/kg	ca. 1085	Rat	Study report (1989)	OECD Guideline 401			
	dermal	LD50 mg/kg	>2000	Rabbit					

# Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

# Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indications of human carcinogenicity exist.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

### STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %))

## STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %))

## **Aspiration hazard**

May be fatal if swallowed and enters airways.

# Specific effects in experiment on an animal

No information available.

# Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].



according to Regulation (EC) No 1907/2006

# Benzine HP 300ml

Revision date: 03.04.2020 Product code: 1100582 Page 9 of 13

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)								
	Acute fish toxicity	LC50 mg/l	10 - 30	96 h	Leuciscus idus (golden orfe)				
	Acute algae toxicity	ErC50 mg/l	4,6 - 10	72 h	Pseudokirchneriella subcapitata				
	Acute crustacea toxicity	EC50 mg/l	10 - 22	48 h	Daphnia magna				
67-63-0	2-Propanol								
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus				
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna				
110-25-8	N-methyl-N-[C18-(unsatu	rated)alkand	oyl]glycine						
	Acute fish toxicity	LC50 mg/l	> 0,43	96 h	Leuciscus idus	REACh Registration Dossier	EU Method C.1		
	Acute algae toxicity	ErC50	5,1 mg/l	72 h	Desmodesmus subspicatus	REACh Registration Dossier	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	0,53	48 h	Daphnia magna	REACh Registration Dossier	EU Method C.2		
	Acute bacteria toxicity	(1300 m	g/l)	3 h	Activated sludge	REACh Registration Dossier	OECD Guideline 209		
95-38-5	2-(2-heptadec-8-enyl-2-in	nidazolin-1-y	/l)ethanol						
	Acute fish toxicity	LC50	0,3 mg/l	96 h	Brachydanio rerio (zebra-fish)				
	Acute algae toxicity	ErC50 mg/l	0,03	72 h	Desmodesmus subspicatus	Study report (2010)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	0,163	48 h	Daphnia magna	Study report (2010)	OECD Guideline 202		

# 12.2. Persistence and degradability

The product has not been tested.

# 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	2-Propanol	0,05
110-25-8	N-methyl-N-[C18-(unsaturated)alkanoyl]glycine	>= 3,5
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	8,4



according to Regulation (EC) No 1907/2006

	Benzine HP 300ml	
Revision date: 03.04.2020	Product code: 1100582	Page 10 of 13

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
	N-methyl-N-[C18- (unsaturated)alkanoyl]glycine	1,98	fish	BCFBAF version 3.01
95-38-5	2- (2-heptadec-8-enyl-2-imidazolin-1-yl)et hanol	371,8		EPIWIN calculation (

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

### 12.6. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### List of Wastes Code - residues/unused products

 $070704 \qquad \text{WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals} \\$ 

and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

# List of Wastes Code - used product

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals

and chemical products not otherwise specified; other organic solvents, washing liquids and mother

liquors; hazardous waste

### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

#### Contaminated packaging

Water (with cleaning agent). Completely emptied packages can be recycled.

## **SECTION 14: Transport information**

# Land transport (ADR/RID)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes,

isoalkanes, cyclics, aromatics (2-25 %), 2-Propanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640C

Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2



according to Regulation (EC) No 1907/2006

Revision date: 03.04.2020 Product code: 1100582 Page 11 of 13

Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes,

isoalkanes, cyclics, aromatics (2-25 %), 2-Propanol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1

Special Provisions: 274 601 640C

Limited quantity: 1 L Excepted quantity: E2

Marine transport (IMDG)

**14.1. UN number:** UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes,

isoalkanes, cyclics, aromatics (2-25 %), propan-2-ol)

14.3. Transport hazard class(es): 3 Ш 14.4. Packing group: Hazard label: 3 Marine pollutant: ves **Special Provisions:** 274 Limited quantity: 1 L Excepted quantity: E2 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1993

**14.2. UN proper shipping name:** FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes,

isoalkanes, cyclics, aromatics (2-25 %), propan-2-ol)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes

Danger releasing substance: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)

14.6. Special precautions for user

Warning: Combustible liquids.

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**



according to Regulation (EC) No 1907/2006

#### Benzine HP 300ml

Product code: 1100582 Revision date: 03.04.2020 Page 12 of 13

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25 %)

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

#### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

## **National regulatory information**

**Employment restrictions:** Observe restrictions to employment for juvenils according to the 'juvenile

> work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 3 - highly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,13,14,15,16.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.





according to Regulation (EC) No 1907/2006

Benzine HP 300ml					
Revision date: 03.04.2020	Product code: 1100582	Page 13 of 13			
H336	May cause drowsiness or dizziness.				
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.				
H372	Causes damage to organs through prolonged or repeated exposure.				
H373	May cause damage to organs through prolonged or repeated exposure.				
H400	Very toxic to aquatic life.				
H410	Very toxic to aquatic life with long lasting effects.				
H411	Toxic to aquatic life with long lasting effects.				
H412	Harmful to aquatic life with long lasting effects.				
EUH066	Repeated exposure may cause skin dryness or cracking.				

#### **Further Information**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)