

## AQS

### FAST, SAFE AND ECOLOGICAL CLEANING AND DEGREASING

- Strong penetrating effect that "lifts" the dirt.
- Universally applicable, non-corrosive, non-flammable. Can be used safely on machines, tools, cooling systems, printing presses, floors, polyester and other synthetic materials.
- Fully biodegradable.
- 100% soluble in water.
- Very economical in use - highly concentrated - dilute with water from 1/1 up to 1/40.
- Can be used for manual as well as for high-pressure cleaning.



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

## AQUASOLV

### GENERAL INFORMATION

AQUASOLV is a concentrate of water-soluble solvents, penetrating agents, wetting agents and synthetic detergents with the ability to attack the molecular structure of soils, greasy deposits, gummy residues and imbedded grease stains without damaging the surface itself. Soils are then detached by capillary action and emulsified for complete removal

by mopping or rinsing. AQUASOLV is completely biodegradable and does not contribute to water pollution. AQUASOLV is non-flammable and non-toxic to humans or pets. AQUASOLV contains a powerful corrosion inhibitor to reduce the hazard of corrosion to steel surfaces which are subject to rusting with most water-based cleaners.

### TECHNICAL INFORMATION AND PACKAGING

Composition: a stabilized concentrate of biodegradable surfactants and penetrants with oxygenated solvents and modified alkalis with no free caustics.

Flammability: non-flammable.

Odour: fresh.

Colour: blue.

PH-factor: 12.9.

Toxicity: non-toxic when used properly, do not take

internally.

Food industry: see H.A.C.C.P. certificate; meets the AOX standard: free of absorbable organic halogens.

CAUTION: FOR PROFESSIONAL USE ONLY -

NEVER USE UNDILUTED!

Shelf life: 12 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

### APPLICATION AND USE

- |                                  |       |   |    |    |    |
|----------------------------------|-------|---|----|----|----|
| • Dilution:                      | A     | B | C  | D  | E  |
| • Parts AQUASOLV:                | 1     | 1 | 1  | 1  | 1  |
| • Parts water:                   | 2     | 5 | 10 | 20 | 40 |
| •                                |       |   |    |    |    |
| • Food processing machinery:     | B / D |   |    |    |    |
| • Presses, Punches, Drills:      | A     |   |    |    |    |
| • Vents and Filters:             | B     |   |    |    |    |
| • Automotive Parts:              | A     |   |    |    |    |
| • Elevators, Guard rails, Safety |       |   |    |    |    |
| • equipment:                     | C     |   |    |    |    |

- |                                |       |
|--------------------------------|-------|
| • Packaging and vending:       | C / D |
| • Machine tools and lathes     | A     |
| • Pulleys, winches and cranes  | B / C |
| • Conveyor belts, drive chains |       |
| • and loading ramps            | B / C |
| • Boats and marine equipment   | B     |
| • Floors                       | D     |
| • Steam cleaning               | D     |
| • Scrubbing machine            | E / D |
| • Periodic Cleaning            | E     |

| Article nr | Name              | Content | Section                 |
|------------|-------------------|---------|-------------------------|
| N491005    | Aquasolv          | 5l      | CLEANERS AND DEGREASERS |
| N491025    | Aquasolv          | 25l     | CLEANERS AND DEGREASERS |
| N491925    | Tap for 25l drums | 1pc.    | TOOLS                   |
| N699900    | Tap for 200l drum | 1pc.    | TOOLS                   |

