

NRF

LASTING ELASTIC, FIBRE-REINFORCED AND WATERTIGHT PROTECTIVE AND SEALING PASTE

- Sealing, repairing, waterproofing and bonding with one product.
- Can be applied on moist surfaces.
- Adheres to most building materials: brick, concrete, wood, lead, copper, tin, bituminous roofing materials, galvanized steel, insulating materials, PVC, polyester.
- Does not harden and remains flexible.
- Very easy to apply, also on small, difficult places, due to cartridge packing.
- Can also be applied at low temperatures -10°C.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

NOVAROOF

GENERAL INFORMATION

NOVAROOF is a sealant with a unique composition. Due to the combination of bitumes, butyl rubber and glass fibres, a product with a very high tensile strength and flexibility is obtained.

NOVAROOF can be applied on most surfaces, also in a moist condition.

TECHNICAL INFORMATION AND PACKAGING

Composition: modified bitumes, glass fibres and butyl rubber.

Elongation at rupture (dry film): 170%.

Temperature resistance: -45°C to +85°C.

U.V. resistance: excellent.

Ageing properties: none during 20 years.

Water resistance: very good in case of a normal draining.

Climatic resistance: excellent.

Resistance to hydrocarbons: non resistant.

Application temperature: -12°C to +50°C.

CAUTION:

DO NOT APPLY ON SNOW OR GLAZE ICE !!!

Shelf life: 24 months, keep dry, cool and frost-proof.

Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- NOVAROOF can be applied on most building materials such as: brick, concrete, wood, lead, copper, tin, bituminous roofing materials, galvanized steel, insulation materials, PVC, polyester.
- TYPICAL APPLICATIONS:
 - all types of roof repairs: sloping and flat roofs, roof gutters, edgings, drain pipes, lead flashings, corrugated plates, also on wet surfaces
 - sealing and finishing off of roof joints, eaves, feedtrough ducts, chimneys
 - as cold adhesive for roof repairs with bituminous roofing materials
 - making waterproof of concrete and brickwork in foundations and terraces
 - corrosion protection of underground pipelines and channels

Article nr	Name	Content	Section
N599610	Novatwister	1 pc.	TOOLS
N602106	Novarroof	310ml	ADHESIVES AND SEALANTS
N602210	Novarroof	10kg	ADHESIVES AND SEALANTS

