### TECH-MASTERS Trading GmbH Perfektastraße 55, A-1230 Wien Tel: +43 (0)1 / 867 29 07 office@tech-masters.com www.tech-masters.eu



on siloxanes for

# SBST

### TRANSPARENT, FLEXIBLE SEALING CEMENT WITH GOOD ADHESIVE QUALITIES

- · Contains no plasticizers.
- Safe to use on natural stone.
- Very high elasticity: 480%.
- Bonds without primer to most materials: natural stone, brick, concrete, ceramics, enamel, acrylate, porcelain, metals, glass, soft and hard wood, ...
- Excellent resistance to fungal growth.
- Brilliant, dirt-repelling joints with
- excellent UV-resistance.
- Easy to squeeze and to handle.



# **SEAL & BOND SEALTRANS**

## **GENERAL INFORMATION**

SEAL & BOND SEALTRANS is a recently developed single component synthetic

rubber polymer based elastic, transparent sealing,

## **TECHNICAL INFORMATION AND PACKAGING**

Character: elastic synthetic rubber based on polysiloxanes. Consistency: paste-like. Colour: transparant - brilliant. Shrinkage: according to DIN 52451 < 1%. Sagging out: according to ISO 7390 less than 1 mm. Max. permitted tranformation: 25% - durable. Shore hardness W : 24 Shore A - according ISO 868. Tensile strength: 130 N/cm2. Elongation at rupture: 600%. E-modul: 100% 0.3 mPa. UV-resistance: excellent.

APPLICATION AND USE

- applicable where elastic, transparent joints are required.
- very appropriate for sealing "problematic" surfaces such as natural stone and acrylate, due to its composition free of plasticizers.
- ideal transparent sealant for use in interior construction, verandas, windows and doors, kitchens and bathrooms as well as in general maintenance.

 Article nr
 Name

 N539096
 Seal & Bond Sealtrans clear cart.

IG

Fungicidal: according to ISO 846. Painting: CAN NOT be painted. Curing: 2 mm / 24 hrs / 23°C 50% R.H. Finish: 5 min. 23°C / 50% R.H. Thermal stability: -45°C to +155°C. Volatile organic compounds (VOC): 0,00%. Organic solvents: 0,00%. Application temperature: from +5°C up to +40°C. Shelf life: 12 months, keep dry, cool and frost-proof. Safety measures: consult the Safety Data Sheet.

 excellent adherence to most surfaces found in the building industry, e.g.: natural stone, brick, concrete, ceramics, enamel, acrylate, porcelain, metals, glass, soft and hard wood ... with the exception of PE - PP - Teflon and bitumen.

Content Section altrans clear cart. 310ml ADHESIVES AND SEALANTS









All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



ADHESIVES AND SEALANTS WWW.TECH-MASTERS.EU