TECH-MASTERS Trading GmbH Perfektastraße 55, A-1230 Wien Tel: +43 (0)1 / 867 29 07 office@tech-masters.com www.tech-masters.eu

FOG

MULTIPURPOSE H1 LUBRICANT FOR FOOD INDUSTRY

- colourless
- reduces friction and wear
- dirt and water repellent
- resistant to hot and cold water
- protects against corrosion
- long service live



GENERAL INFORMATION

FOOD GEL is a physiologically harmless multipurpose grease that meets the requirements for a lubricant in food processing. FOOD GEL resists water and salt solutions in operating temperatures of -15 °C to +130 °C. In contact of lubricant with food or

TECHNICAL INFORMATION

Color: colourless Odor: odourless Thickener: Inorganic Base oil: Medical white oil, synthetic KW Base oil viscosity at 40 °C: Approximately 200 mm²/s Viscosity index: > 100 Service temperature range: -15 °C to +130 °C

APPLICATION AND USE

Appliaton:

Article nr

T202001

FOOD GEL is used in all types of food establishments in the manufacturing, processing, storage and final preparation of food and beverage.

FOOD GEL is widely used in meat factories, canneries, bakeries, kitchens and restaurants, dairies, bottling plants, food warehouses and breweries. Furthermore, it is used in water plants, agriculture, forestry and in other companies, where the use of conventional lubricants and their eventual release into the environment could cause environmental damage or accidents FOOD GEL can be used for lubrication of rolling bearings, plain bearings and other mechanical parts.

Name

Food Gel

with a raw material, must be contaminated part removed and cannot be used for human con- sumption. FOOD GEL is biodegradable over 90% and offers a very good lubricating and durability. It also features excellent anticorrosive and protective properties.

(briefly +150 °C) Initial boiling point and boiling range: 218 °C Flash point: 170 °C VKA: 2.200 N Density (at 20 °C): 0,9 g/cm³ Safety measures: consult the Safety Data Sheet.

Use:

Content

400g

Thoroughly clean the places to be lubricated first. Apply thinly and and evenly to the parts to be lubricated. Fill roller bearings only to a maximum of 80%. Only fill to 60% of the bearing volume at most in the high temperature range (observe the rules laid down by the bearing maker).

Section

LUBRICANTS



NOTE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.







FOOD GEL