TECH-MASTERS Trading GmbH
Perfektastraße 55, A-1230 Wien
Tel: +43 (0)1 / 867 29 07
office@tech-masters.com
www.tech-masters.eu

SUX

SEALFLUX

NOVATIO'S REVOLUTIONARY WATERPROOF SHRINK CONNECTION

- Cable connector provided with wear-resistant nylon insulation and meltable adhesive.
- Shrink ratio of the insulation 2:1.
- Vibration resistant with a high tensile strength.
- High temperature resistance.
- Fast and handy to use.
- Highly resistant to wear and vibrations.
- Resistant to hydraulic oil, solvents, diesel fuel, petrol, salt water, battery acids, brake fluid, ...
- High insulation resistance.
- 3 transparent colour codes for various diametres with verification of the connection.



GENERAL INFORMATION

SEALFLUX insulates and protects electrical connections from mechanical abuse and wire pull-out.
SEALFLUX provides a tough, environment friendly sealed wire connection. Their crimp barrel or terminal, encased in a rugged nylon tubing with a special hot-melt adhesive, resists damage from abresions and cuts.
SEALFLUX retains its flexibility and impact-resistance long after similar products have become brittle.
The colours of SEALFLUX are coded to easily identify the wire diameter, yet they are transparent for the inspection of the finished connection.

TECHNICAL INFORMATION AND PACKAGING

Insulation resistance: Megohms 103.
Dielectric resistance: 2,5 Kilovolt.
Chemical resistance: diesel fuel, brake fluid, antifreeze, 5% salt water, motor oil, ...
Solvent resistance: isopropyl alcohol, trichloroethylene, gasoline.
Constant temperature: from -55°C to 125°C.
Minimum shrink temperature: 180°C.
Voltage rating: 600 Volt maximum.
Shrink ratio: approximately 2:1.
Electrical properties: disruptive strength 1000 Volt; insulation resistance: 103 Megohms.

APPLICATION AND USE

- garage and bodywork
- built-in car radios and alarm systems
- assembling of towing hooks
- lorry and bus manufacturers
- contract workers, farmers, earth-moving machines
- signalisation and neon lights
- horticulture and outdoor lighting
- electric installation and maintenance services
- repair of tools and machines
- industrial maintenance services
- motorbikes and mopeds
- shipbuilding and -repair
- amusement parks

Article nr	Name	Content	Section
N831010	Sealflux Interconnectors red	1pc.	ELECTRICAL CONNECTIONS
N831020	Sealflux Interconnectors blue	1pc.	ELECTRICAL CONNECTIONS
N831030	Sealflux Interconnectors yellow	1pc.	ELECTRICAL CONNECTIONS
N832120	Sealflux Ring blue 10,5mm	1pc.	ELECTRICAL CONNECTIONS
N832130	Sealflux Ring yellow 10,5mm	1pc.	ELECTRICAL CONNECTIONS
N832410	Sealflux Ring red 4,3mm	1pc.	ELECTRICAL CONNECTIONS
N832420	Sealflux Ring blue 4,3mm	1pc.	ELECTRICAL CONNECTIONS
N832510	Sealflux Ring red 5,3mm	1pc.	ELECTRICAL CONNECTIONS
N832520	Sealflux Ring blue 5,3mm	1pc.	ELECTRICAL CONNECTIONS
N832530	Sealflux Ring yellow 5,3mm	1pc.	ELECTRICAL CONNECTIONS
N832610	Sealflux Ring red 6,5mm	1pc.	ELECTRICAL CONNECTIONS
N832620	Sealflux Ring blue 6,5mm	1pc.	ELECTRICAL CONNECTIONS
N832630	Sealflux Ring yellow 6,5mm	1pc.	ELECTRICAL CONNECTIONS
N832820	Sealflux Ring blue 8,4mm	1pc.	ELECTRICAL CONNECTIONS
N832830	Sealflux Ring yellow 8,4mm	1pc.	ELECTRICAL CONNECTIONS
N833410	Sealflux Fork red 4,3mm	1pc.	ELECTRICAL CONNECTIONS
N833420	Sealflux Fork blue 4,3mm	1pc.	ELECTRICAL CONNECTIONS
N833520	Sealflux Fork blue 5,3mm	1pc.	ELECTRICAL CONNECTIONS
N833530	Sealflux Fork yellow 5,3mm	1pc.	ELECTRICAL CONNECTIONS
N834410	Seaflux Slide Plug Female red	1pc.	ELECTRICAL CONNECTIONS
N834610	Sealflux Slide Plug Female red	1pc.	ELECTRICAL CONNECTIONS
N834620	Sealflux Slide Plug Female blue	1pc.	ELECTRICAL CONNECTIONS
N834630	Sealflux Slide Plug Female yellow	1pc.	ELECTRICAL CONNECTIONS
N835610	Sealflux Slide Plug Male red	1pc.	ELECTRICAL CONNECTIONS
N835620	Sealflux Slide Plug Male blue	1pc.	ELECTRICAL CONNECTIONS
N836010	Sealflux Tulip Female red	1pc.	ELECTRICAL CONNECTIONS
N836020	Sealflux Tulip Female blue	1pc.	ELECTRICAL CONNECTIONS
N836110	Sealflux Tulip Male red	1pc.	ELECTRICAL CONNECTIONS
N836120	Sealflux Tulip Male blue	1pc.	ELECTRICAL CONNECTIONS

NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.