

## TMY

### THE PERFECT WAY TO INDICATE AND INSULATE EARTHING

- Flame retardant.
- Good temperature resistance (+300°C).
- Very good chemical resistance.
- Has a high disruptive strength 20 Mv/m.
- Quick, easy and safe to use.



## THERMOFLUX YELLOW/GREEN

### GENERAL INFORMATION

THERMOFLUX YELLOW/GREEN is a flexible, flame retardant tubing, designed to indicate earthing and to apply permanent markings to wires and cables. THERMOFLUX YELLOW/GREEN has a very good temperature resistance.

With peaks up to 300°C.  
THERMOFLUX YELLOW/GREEN has a high disruptive strength of 20 MV/m.  
THERMOFLUX YELLOW/GREEN has a good chemical resistance to most fluids and solvents.

### TECHNICAL INFORMATION AND PACKAGING


Temperature resistance: -55 + 150°C.  
Shrink temperature: 120°C.  
Krimpverhouding: 2/1.  
Tensile strength: 7 MPa.  
Ultimate elongation ISO 37: 200%.  
Flexibility: flexible.

Dielectric strength IEC 243: 20 MV/m.  
Flame retardancy ASTM D 876, UL 224.  
Fluid resistance ISO 37 immersion 24h at 23°C:  
lubricating oil ISO 1817: fluid 101  
Esters ISO 1817: fluid 103.

### APPLICATION AND USE

- indication of earthing on wires, cables, rods and slats, ...
- protection of cables and components

Article nr	Name	Content	Section
N806412	Thermoflux Yellow/Green 2010 12,7/6,35mm	1pc.	ELECTRICAL CONNECTIONS
N824110	Thermoflux Yellow/Green 3,0mm/1,5mm	1 pc.	ELECTRICAL CONNECTIONS
N824120	Thermoflux Yellow/Green 6mm/3mm	1 pc.	ELECTRICAL CONNECTIONS
N824130	Thermoflux Yellow/Green 8mm/4mm	1 pc.	ELECTRICAL CONNECTIONS
N824160	Thermoflux Yellow/Green 19mm/8,5mm	1 pc.	ELECTRICAL CONNECTIONS
N824170	Thermoflux Yellow/Green 26mm/13mm	1 pc.	ELECTRICAL CONNECTIONS
N824180	Thermoflux Yellow/Green 38mm/19mm	1 pc.	ELECTRICAL CONNECTIONS



### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

