### **TECH-MASTERS Trading GmbH** Perfektastraße 55. A-1230 Wien Tel: +43 (0)1 / 867 29 07 office@tech-masters.com www.tech-masters.eu



# SAG

## SPRAYABLE ANTI SLIP COATING

- · Make all surfaces anti-slip
- Transparent colour
- Simple, time saving application
- Removable
- Good UV resistance
- Part-time and permanent use
- Can be colored with acrylic paint



## **GENERAL INFORMATION**

SAFETY GRIP SPAY is a transparent coating with anti-slip-particles. SAFETY GRIP SPAY is ideal for floors, steps, balustrade, handles and all other applications where surfaces have to be prepared with a safe grip. For

#### **TECHNICAL INFORMATION**

#### Form: Aerosol

Color: Colorless Odor: Characteristic Degree of gloss: (at measurement angle 60° acc. to DIN 67530) glossy: >15 gloss units Efficiency: Depending on consistence and color of the ground: 500 ml are sufficient for 1,5 - 2,5 m<sup>2</sup> Drying time (at 20°C, 50% relative air humidity): Dust-dry: after approx. 10 minutes Dry to touch: after approx. 30 minutes Ignition temperature: 333°C Lower explosion limit: 1 Vol% Upper explosion limit: 13 Vol%

## **APPLICATION AND USE**

- · The surface must be clean, free of gease and dust •
- Shake can carefully for 2 minutes Carry out spray for testing.

. .. .

The structural density and effect is depending on the n

	ensity and effect is depending on coats and the spraying distance	Powersolv or Megac	lean
nr	Name	Content	Section

Article nr	Name	Content	Section
T166001	Safety Grip Spray	400ml	SURFACE PROTECTION AND
			TREATMENT







· Apply several thin layers



#### NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



SURFACE PROTECTION AND TREATMENT WWW.TECH-MASTERS.EU

SAFETY GRIP SPRAY

all out- and indoors applications and for most surfaces like cement, stone, screed, asphalt, clinker, ceramictile, metal and so on.

SAFETY GRIP SPRAY is your product for preparing a safe and anti-slip surface.

Vapour pressure (at 20°C): 8300 hPa (6225,5 mm Hg) Density (at 20°C): 0,75 g/cm<sup>3</sup> Organic solvents: 88% VOC-content: 660,0 g/l (88,01%) Solids content: 12% The drying time depends on surrounding temperature, air humidity and thickness of the applied coat. Temperature resistance: to 80°C UV resistance: good Shelf life: 10 years if appropriate storage provided (= 10°C - 25°C, relative air humidity of max. 60%

Can be colored with all acrylic paints (wet in wet)

Safety Grip Spray can be removed by Supersolv,