

TPR

CLEAR PRIMER TO IMPROVE ADHESION OF GLUE AND PAINT

- Excellent for very flexible synthetic materials
- Ideal before application of paints and primers
- It can be used for MS-, PU- and MMM-adhesives and adhesives tapes
- Easy application



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

TECHNO PRIMER

GENERAL INFORMATION

TECHNO PRIMER has been developed especially developed to improve adhesion on difficult materials such as synthetic materials based on PP or PPE.

TECHNO PRIMER is used optimally in the automotive sector, for example for the

adhesion promoter on bumpers and plastic parts for the application of paints and primers. You should always test the product before you apply it over large areas. Not suitable for very porous surfaces.

TECHNICAL INFORMATION

Technical Information
 Colour: Transparent
 Drying time: 20-30 minutes at +20 ° C
 Working temperature: +10 ° C
 Autoinflammability: 435 ° C

Relative density: 0.90 + / -0.5%
 Water solubility: NO
 Storage: 18 months from date of manufacture
 Keep in a cool and dry place

APPLICATION AND USE

- Ideal for application on smooth surfaces and not very porous.
- Clean the surfaces with MULTIFOAM or Safety Clean.
 Ensure surfaces are dry and free of dirt and grease.
 Shake the can for 2-3 minutes.
 Apply in thin layers.
 Observe the drying times and apply the adhesive (glue or tape).
- After use, turn the can to 360 ° and spray to clean the nozzle.

Article nr	Name	Content	Section
------------	------	---------	---------

