

NPC

DURABLE PTFE-TREATMENT FOR ENGINE, GEARBOX AND DIFFERENTIAL

- Prevents metal-metal friction by the PTFE-formula.
- Protects all lubricating, rotating and moving parts.
- Prolongs the life span of the engine, gearbox and differential.
- Appropriated for diesel and petrol engines.
- Applicable in all manually changed gearboxes.
- Prevents sludge and protects against acids.
- Increases the performance capacity of the car.
- Reduces exhaust emission.
- Works efficiently and durable.
- A PTFE-treatment does not require working hours.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

NOVA PTFE CARE

GENERAL INFORMATION

NOVA PTFE CARE is a durable PTFE-treatment for engine, gearbox and differential.
 NOVA PTFE CARE is formulated for the heaviest performances, 1 treatment is sufficient for 80,000 km.
 NOVA PTFE CARE is a concentrated friction reducer and improves the

durability of the engine.
 NOVA PTFE CARE prolongs the life span of all moving parts of the engine, gearbox and differential by covering them with a PTFE-film that prevents friction.
 NOVA PTFE CARE reduces the oil consumption.

TECHNICAL INFORMATION AND PACKAGING

Boiling point: 48 °C.
 Flashpoint: 215 °C.
 Melting point: 300 °C.
 pH: 4 - 8.
 Relative density (at 20°C): 0,89.
 Relative vapour density: > 1.
 Water solubility: insoluble.

Odour: ether-like.
 Colour: colourless.
 NOVA PTFE CARE treats up to 5 litres of oil.
 Shelf life: 12 months, keep dry, cool and frost-proof.
 Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- Bring the engine at operating temperature.
- Add half of the bottle in the engine to the clean engine oil.
- Shake the bottle powerfully and add the rest.
- For optimal result: clean first with NOVAFLUSH ENGINE.

Article nr	Name	Content	Section
N741403	Nova PTFE Care	300ml	ADDITIVES
N741900	Nova-Tuit	1pc.	TOOLS



ADDITIVES

WWW.TECH-MASTERS.EU

