

NTA

TRANSPARENT AND SELF-ADHESIVE PU-FILM

- High quality polyurethane film with acrylic glue.
- Protects against chemical pollution, grit, rust, scratches, ...
- Protects against wear by vibration and friction.
- Thanks to elasticity of 75% many shapes can be formed.
- Temperature resistance of -40°C to +90°C.
- Long-life product.
- Ideal on hard surface.
- Can be lacquered and/or varnished.
- Protects aluminium, stainless steel, chromium plate, PU, glass, lacquer, acrylic plastic, ABS, ...
- Prevents squeeking and improves the impact resistance.



NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.

NOVA CLEAR TAPE

GENERAL INFORMATION

NOVA CLEAR TAPE is a high quality, transparent polyurethane film with acrylic glue.
NOVA CLEAR TAPE adheres to most synthetics, lacquers, types of

metal,... and protects against rust, grit, scratches, friction, vibration,...
NOVA CLEAR TAPE is 100% transparent and can be moulded and painted.

TECHNICAL INFORMATION AND PACKAGING

Film: polyurethane.
Glue: acrylic glue.
Colour: transparent.
Application temp.: +8°C to +50°C.
Temp. resistance: -40°C to +90°C.
Tensile strength: 13,5 N/mm².
Elasticity: > 75%.
Conservation of quality: for 7 years.
Adherence to: raw aluminium, anodised aluminium, stainless steel, chromed steel, polyurethane, glass, acrylic, ABS, ...
Important: do not apply on soft surfaces or surfaces that can brake, peel, shrink or expand.

Time	Grade	Bonding
20 min.	90°	> 900 N/m
20 min.	180°	> 600 N/m
24 uur.	90°	> 530 N/m
24 uur.	180°	> 700 N/m

First test foundations based on PE, PP, silicones and bitumen for adhesion (see each tape).
Shelf life: 24 months, keep dry, cool and frost-proof.
Safety measures: consult the Safety Data Sheet.

APPLICATION AND USE

- Protects against:
 - scratches
 - rust
 - grit
 - friction
 - vibrations

Article nr	Name	Content	Section
N566315	Nova Clear Tape 15cm x 200cm	1pc.	TAPES



TAPES

WWW.TECH-MASTERS.EU

