

VBT

SAFE, QUICK AND EASY BUNDLING AND TYING

- Ultra thin hook and loop.
- Easy to use with low peeling force resistance.
- High tensile strength with an optimised hookloop connection.
- High material strength due to the special polypropylene.
- Also safe to use on most sensitive materials thanks to its soft finish.
- For indoor and outdoor use, with good humidity and weather resistance.
- Available in two colours: black for neutral bundling and tying, fluorescent yellow for noticeably safer tying.
- Comes with a handy dispenser with belt clamp and cutting blade.

GENERAL INFORMATION

HL-FIX BT is a very fine polypropylene HL-Fix for tying and bundling. This special technology allows for a low peeling force resistance, which guarantees user friendliness that directly opposes its high tensile strength. The soft finish respects the most sensitive materials and even plants. Its humidity and weather resistance makes it perfect to use indoors as well as outdoors.

TECHNICAL INFORMATION AND PACKAGING

Carrier: polypropylene Width: 15 mm Length: 3 m Average peeling force: new tape: 88,84 g/cm² After 3000 closings: 67,11 g/cm² Average tensile strength: new tape: 1,46 kg/cm² After 3000 closings: 1,31 kg/cm²

HL-FIX BT can be open and closed hundreds of times.

The greater the overlap, the stronger the connection.

fluorescent yellow. The black version is used to bundle

and tie neutrally, while the fluorescent yellow version

makes it all noticeable. The handy HL-FIX BT dispenser

is small and comes with a belt clamp and a cutting

HL-FIX BT is available in two colours: black and

Article nr	Name	Content	Section
N562815	HL-Fix Bundle & Tie yellow 15mm x 3m	1pc.	TAPES
N562915	HL-Fix Bundle & Tie black 15mm x 3m	1pc.	TAPES
N562999	HL-Fix Bundle & Tie Dispenser	1pc.	TAPES

blade.

HL-FIX BUNDLE





NOTICE

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Novatio is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Novatio products provide, relates only to the standard conditions of sale of this product. In no case Novatio can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.





WWW.TECH-MASTERS.EU