

LTP-T

EASY TO USE BLOWTORCH WITH SWIVEL BURNER FOR HANDS-FREE WORKS

- Automatic ignition guaranteed for 30 000 ignitions
- Strong metal piezo cover for long lasting durability
- 360° swivel burner for hard to reach places
- Compact and stable cyclone flame
- · Burner i high quality stainless steel
- Changeable and optional burners
- Valve body in brass with a protective nickel plating
- · Built in regulator 0-3,5 bar
- Provides a temperature of 1925°C -2400°C



LOTPISTOLE TURBO

GENERAL INFORMATION

For all kinds of brazing, soft soldering and heating applications. Available with piezo ignition.

TECHNICAL INFORMATION

Working pressure: 0-3,5 bar Burnerdiameter: 14 Gas consumption at 2 bar: 295

Effect: 3,8 kw

Soft soldering: 40 mm Brazing max. 14 mm

TECHNICAL INFORMATION CARTRIDGE AND BURNER

- Powergas 2203, 2204: Disposable cartridges 2203 and 2204 with self closing valve. Contains a gas mixture of 35% propane and 65% butane.
- Ultragas 2205: High efficient gas with built-in anti flare function . Disposable cartridges with self closing valve. Contains a gas mixture of propane, butane, propene and acetone. Weight: 450 g, Content: 336g / 600 ml.
- Ultramapp 2206: New unique gas mixture with increased flame temperature 2400°C. Disposable light weight aluminium cartridge with self closing valve. Environmental friendly, non-toxic gas mixture. Weight: 640 g, Content: 393 g/750 ml.
- Premium Quality propane 2208: Disposable light weight aluminium cartridge with self closing valve. Weight: 640 g, Content: 380 g/750 ml.

 Cyclon burner 2630: For all kinds of brazing, soft soldering and heating applications • Available with and without piezo ignition.

Burner diameter: 14mm Gas consumption: 295g/h Effect: 3.8kW

Soft soldering max diameter: 40mm Brazing max diameter: 18mm.

 Turbo burner hot air 2632: For shrinking and paint stripping

Purpose diameters 38 mm

Burner diameter: 38 mm Gas consumption: 180g/h Effect: 2,3 kW

Twin cyclon burner 2633: For all kinds of brazing, soft soldering and heating applications. Twin construction for double speed.
 Burner diameter Ø, mm 2x14
 Gas consumption, g/h 590
 Effect, kW 7,6
 Soft soldering max Ø, mm 60
 Brazing max Ø, mm 25

Article nr	Name	Content	Section	
Y902203	Powergas 1925°C	300ml	TOOLS	
Y902204	Powergas 1925°C	600ml	TOOLS	
Y902205	Ultra Gas 2100°C	380ml	TOOLS	
Y902206	Ultramapp 2200°C	750 ml	TOOLS	
Y902207	Gas Ultra 2100° C	400 ml	TOOLS	
Y902208	Propanegas 1925°C	750ml	TOOLS	
Y902630	Cyclon Burner Turbojet	1 pc.	TOOLS	
Y902632	Turbo Hot Air Burner	1 pc.	TOOLS	
Y902633	Turbojet Cyclon Burner Double	1 pc.	TOOLS	











T902203 T902204 T902205 T902206 T902208



All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.









T908843



