

### Automotive

## **AUTOSEAL MS**

## **AUM-S**

# SPRAYABLE SEALING AND BONDING MATERIAL BASED ON MS POLYMER.

- Sealant for metal plates based on MS Polymers
- Excellent adhesive power sprayable
- It contains no silicon and isocyanides
- Paintable with the most of the enamels
- It is possible to restore the sealing and bonding in their original state
- Fast polymerization
- · Direct paintable
- The open cartridge keeps for a long time

#### **GENERAL INFORMATION**

AUTOSEAL MS is a sealant based on MS polymer with high adhesive power.

AUTOSEAL MS can be applied both in thin and thicker layers: both can be refined with

a brush, restoring the sealing in their original state.; it can be also sprayed. AUTOSEAL MS contains less than 7% of aliphatic

#### **TECHNICAL INFORMATION AND PACKAGING**

At 23°C / 50% R.H.
Base: MS Polymer
Colour: Grey, Beige
Consistency: sprayable
Density: 1,540kg/m3
Curing (23°C / 50% R.H.):

3 mm in 24 hours, 5mm in 48 hours.

Skinning time: 15 min E-modulo 100% Mpa: 0,85 Temperature resistance: -40°C to +90°C Mechanical resistance: 125 Nw

Elongation at break: >250% Hardness (Shore A): 40

solvents; it is quite odorless.

#### **APPLICATION AND USE**

- AUTOSEAL MS has been designed to restore all the sealing of the metal plates in the automotive industry.
- AUTOSEAL MS is suitable to seal inside the engine compartment, along the edge of the bonnet, in the doors, inside the luggage compartment, in the wheels etc... The product ensures a perfect holding because of its adhesive and elastic power; it reduces vibrations and noises.
   Soundproofing and anticorrosive.
- The product can be applied on different kind of surfaces besides the metallic ones, in fact it adheres also on different synthetic materials, glass and plexi. It
- slightly adheres on PP, PE, PPE PTFE
   USE: the product must be applied on clean,
   degreased and dry surfaces.

Article nr Name Content Section

#### **NOTICE**

All information including images are given with the greatest care. Still, it is appropriate to users regardless of the test the suitability of each product for their own purposes. Tech-Masters is not liable for the completeness and accuracy of information and refuses warranty for your specific use. The guarantee, which Tech-Masters products provide, relates only to the standard conditions of sale of this product. In no case Tech-Masters can be held responsible for incidental damages, or damages for improper use or sale of the product to another customer.



